

#### SAFETY DATA SHEET

(Following Regulations (EC) No 1907/2006 & (EC) No 1272/2008)

SDS Number: 750 Date of first issue: 20 April 2015 Date of last revision: 21 February 2022

## 1 - Identification of product

## 1.1 - Identification of Product

Tradenames: WDS Contour, WDS Flexible Kontur, WDS LambdaFlex, WDS LambdaFlex D, WDS LambdaFlex Super, WDS LambdaFlex Super HT, WDS SuperFlex,

1.2 - Use of Product

### Relevant identified uses of the substance or mixture:

Insulating material

Sector of use [SU]: SU 3 - Inudstrial uses: Uses of substances as such or in preparations at industrial sites

# Uses advised against:

No information available at present

## 1.3 - Identification of Company

# Distributor:

THERMAL CERAMICS LIMITED Tebay Road, Bromborough, Wirral, CH62 3PH, UK	Porextherm Dämmstoffe GmbH, Heisinger Str. 8/10, D87437 Kempten Germany

Tel. : +44 (0) 151 334 4030 Fax : +44 (0) 151 334 1684 Telephone: +49 (0)831-575360 Fax: +49 (0)8310575363 www.porextherm.com,

info@porextherm.com

Manufacturer:

#### Website

www.morganthermalceramics.com sds.tc@morganplc.com

### 1.4 - Emergency information

Tel: + 44 (0) 7931 963 973 Language: English Opening hours: Only available during office hours

## 2 - Hazard Identification

## 2.1 - Classification of the substance/ mixture

2.1.1 CLASSIFICATION ACCORDING TO REGULATION (EC) NO 1272/2008

Not classified as hazardous according to Classification, Labelling and Packaging regulations (CLP) 1272/2008 EEC

#### 2.2 - Labelling Elements

No labelling required as product is considered an article under REACH and CLP regulations.

### 2.3 - Other hazards which do not result in classification

The product does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006

The product does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006

# 3 - Composition / Information On Ingredients

COMPONENT	%	CAS Number	REACH Registration Number	Hazard Classification according to CLP
Fumed Silica	50-70	7631-86-9	Not yet available	Not classified
Silicon Carbide	10-30	409-21-2	Not yet available	Not classified
Calcium Silicate	10-30	10101-39-0	Not yet available	H319 - causes serious eye irritation
Silica Fibre	<10	N/A	Not yet available	Not classified

None of the components are radioactive under the terms of European Directive Euratom 96/29.

## 4 - First-Aid measures

#### Skin

In case of skin irritation rinse affected areas with water and wash gently. Do not rub or scratch exposed skin.

## Eyes

In case of eye contact flush abundantly with water; have eye bath available. Do not rub eyes. Seek medical attention is irritation persists.

### Nose and Throat

Typically no exposure pathway.

If symptoms persist, seek medical advice.

4.2 - Most Important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

#### 4.3 - Indication of any immediate medical attention and special treatment required

No special treatment required, if exposure occurs wash exposed areas to avoid irritation.

5 - Fire-fighting measures

### 5.1 - Extinguishing media

Use extinguishing agent suitable for surrounding combustible materials.

### 5.2 - Special hazards arising from the substance or mixture

Non combustible products. However, virgin product encapsulation may burn and produce gases and/or fumes.

### 5.3 - Advice for firefighters

In case of fire involving virgin materials do not breathe fumes Use protective respirator with independent air supply. Dispose of contaminated extinction water according to offical regulations

#### 6 - Accidental Release Measures

6.1 - Personal precautions, protective equipment and emergency procedures

Avoid build up of dust

6.2 - Environmental precautions

Normally not necessary

### 6.3 - Methods and materials for containment and clean up

Pick up mechanically and dispose of according to Section 13

### 6.4 - Reference to other sections

For further information, please refer to sections 7 and 8

# 7 - Handling and storage

## 7.1 - Precautions for safe handling

Avoid build up of dust Eating, drinking, smoling as well as food storage is prohibited in the work-room. General hygiene measures for handling of chemicals are applicable Wash hands before breaks and at end of work Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

# 7.2 - Conditions for safe storage

Store in original packaging in a dry area. Always use sealed and clearly labelled containers. Avoid damaging containers. Reduce dust emission during unpacking.

### 7.3 - Specific end use

Please refer to your local Morgan Thermal Ceramics' supplier.

# 8 - Risk Management Measures / Exposures Controls / Personal Protection

### 8.1 - Control parameters

Industrial hygiene standards and occupational exposure limits vary between countries and local jurisdictions. Check which exposure levels apply to your facility and comply with local regulations. If no regulatory dust or other standards apply, a qualified industrial hygienist can assist with a specific workplace evaluation including recommendations for respiratory protection. Examples of national OELs (November 2014) are given in the table below.

COUNTRY		Resp Dust (mg/m <sup>3</sup> )	Silica (total)	Amorphous Silica (resp)	Aluminium Oxide (total)	Zirconium compounds (resp)	Source
	(mg/m )	(	(mg/m <sup>3</sup> )	(mg/m <sup>3</sup> )	(mg/m³)	(mg/m³)	
India	10	-	-	-	5		Directorate General Factory Advice Service & Labour Industries (DFGASLI)
China	8	-	1	0.7			GBZ 2.1-2019
Japan	8	4	2	1	2		The Japan Society for Occupational Health (JSOH)
South Korea	10	-	10	0.1	10	5	K-OSHA Value
UAE	10	2	10	3	-	5	Abu Dhabi Occupational Safety and Health System Framework (OSHAD-SF) v 3.0 July 2016
Australia	10	2	10	2	10	10	Workplace Exposure Standards for Airbourne Contaminants, Dec 2019

## Information on monitoring procedures

#### United Kingdom

MDHS 14/4 - "General methods for sampling and gravimetric analysis of respirable, thoracic and inhalable aerosols"

#### NIOSH

NIOSH 0500 "Particulates not otherwise regulated, total" NIOSH 0600 "Particulates not otherwise regulated, respirable"

# 8.2 - Exposure controls

8.2.1 APPROPRIATE ENGINEERING CONTROLS

Review your applications in order to identify potential sources of dust exposure. Local exhaust ventilation, which collects dust at source, can be used. For example down draft tables, emission controlling tools and materials handling equipment. Keep the workplace clean. Use a vacuum cleaner. Avoid brushing and compressed air.

If necessary, consult an industrial hygienist to design workplace controls and practices. The use of products specially tailored to your application(s) will help to control dust. Some products can be delivered ready for use to avoid further cutting or machining. Some could be pretreated or packaged to minimise or avoid dust release during handling. Consult your supplier for further details

#### 8.2.2 - Personal Protective Equipment

Eye/face protection: Normally not necessary

Skin protection: Normally not necessary If applicable leather gloves and protective working garments (e.g. safety shoes, long-sleeved protective working garments)

### Respiratory protection:

Normally not necessary If OEL's are exceeded, if applicable, filter P2 (EN143), observe wearing time limitations for respiratory protection equipment.

### 8.2.3 - Environmental Exposure Controls

Refer to local, national or European applicable environmental standards for release to air water and soil. For waste, refer to section13

# 9 - Physical and chemical properties

Information on basic physical and chemical properties	Not applicable
State	Grey solid
Colour	Not applicable
Odour	None
Odour threshold	Not Applicable
pH	Not applicable
Melting point/freezing point	> 1200°C
Initial boiling point and boiling point range	Not applicable
Flash point	Not applicable
Evaporation rate	Not Applicable
Flammability (solid, gas)	Not applicable
Upper/lower flammability or explosive limits	Not applicable
Vapour pressure	Not applicable
Vapour density	Not Applicable
Relative density	150-600 kg/m3
Solubility(ies)	Not soluble in water
Partition co-efficient: n-octanol/water	Not applicable
Auto-ignition temperature	Not applicable
Decomposition temperature	Not Applicable
Viscosity	Not Applicable
Other safety information	Not applicable
Particle Characteristics	Not applicable
Explosive properties	Not applicable
Oxidising properties	Not applicable
10 - Stability and Reactivity	

# 10.1 - Reactivity

The material is stable and non reactive.

#### 10.2 - Chemical Stability

Stable under normal temperature conditions.

## 10.3 - Possibility of Hazardous Reactions

None

#### 10.4 - Conditions to Avoid

Please refer to handling and storage advice in Section 7

### 10.5 - Incompatible Materials

None

### 10.6 - Hazardous decomposition products

Products with encapsulation (PE foil, glass cloth), will, on initial heating above 150°C, release a limited quantity of carbon dioxide, carbon monoxide and traces of other organic compounds. During this initial heating any organic components in the encapsulation will be burned off and subsequent heating will not release any hazardous decomposition materials.

#### 11 - Toxicological information

### Toxicokinetics, metabolism and distribution

#### **11.1.1 BASIC TOXICOKINETICS**

Exposure is not expected during normal use due to nature of the products, exposure during removal may be possible, predominantly by inhalation or ingestion, available toxicological information is as follows:

11.1.2 HUMAN TOXICOLOGICAL DATA

No clear evidence of lung problems is attributable to exposure to alumina particles in spite of widespread and, in some cases, substantial exposure in various sectors of industry.

### 11.1 - Information on hazard classes as defined in Regulation (EC) No 1272/2008

ACUTE TOXICITY

Lethal dose 50 % (LD50) >5000 mg/kg Rat OECD 401 (acute oral toxicity)

Lethal concentration 50% (LC50): 7.6 mg/l/1h Rat OECD 403 (acute inhalation toxicity)

## EXPERIMENTAL STUDIES

In animal studies, no fibrosis or other lung effects was observed following repeated inhalation exposure levels of 20 mg/m<sup>3</sup> and above. Although some absorption may occur from inhaled particles, there is no evidence that this is sufficient to cause systemic effects and any link with Alzheimer's disease is considered to be remote.

# 12 - Ecological information

### 12.1 - Toxicity

These products are inert materials that remain stable overtime.

No adverse effects of this material on the environment are anticipated.

# 12.2 - Persistence and degradability

Not established

12.3 - Bioaccumulative potential

Not established

12.4 - Mobility in soil

No information available

# 12.5 - Results of PBT and vPvB assessment

This mixture contains no substance considered to be persistent, bioaccumulating nor toxic (PBT).

This mixture contains no substance considered to be very persistent and very bioaccumulative (vPvB).

# 12.6 - Endocrine Disrupting Properties

No additional information available

#### 12.7 - Other adverse effects

13 - Disposal Considerations	
13.1 - Disposal Considerations	
14 - Transport information	
14.1 - Transport information	
15 - Regulatory information	
15.1 - Regulatory information	
16 - Other Information	

16.1 - ADDITIONAL INFORMATION AND PRECAUTIONS TO BE CONSIDERED UPON REMOVAL OF AFTER SERVICE MATERIAL

16.2 - uses advised against

16.3 - NOTE

16.4 - Further Information

16.5 - Technical Datasheets

16.6 - Revision Summary

16.7 - NOTICE