



SAFETY DATA SHEET

(Following Regulations (EC) No 1907/2006 & (EC) No 1272/2008)

SDS Number: 1022 Date of first issue: 24 September 2019 Date of last revision: 21 February 2022

1 - Identification of product

1.1 - Identification of Product

Tradenames: Superwool Sealcoat XTra,

The above-mentioned product contains Man-made Vitreous Fibre (MMVF)
Registration number: 01-2119962882-26-0000

1.2 - Use of Product

Application as thermal insulation, heat shields, heat containment, gaskets and expansion joints in industrial furnaces, ovens, kilns, boilers and other process equipment and in the aerospace, automotive and appliance industries, and as passive fire protection systems and fire stops. (Please refer to specific technical data sheet for more information)

1.3 - Identification of Company

IDENTIFICATION OF THE MANUFACTURER/SUPPLIER

Murugappa Morgan Thermal Ceramics Ltd.,
Plot No: 26 & 27, SIPCOT Industrial complex,
Ranipet, Vellore District, Tamil Nadu, India
Pin: 632403

Murugappa Morgan Thermal Ceramics Ltd.,
Plot No: 681, Motibhoyan Village,
Sanand-Kalol state Highway, Kalol Taluk,
Gandhi Nagar District, Gujarat, India

Website

www.morganthermalceramics.com
sds.tc@morganplc.com

1.4 - Emergency information

EMERGENCY CONTACT NUMBER

Tel 1: +91 (4172) 244 313 extn no. 215 or 201
Language: English

Opening hours: Only available during office hours

2 - Hazard Identification

2.1 - Classification of the substance/ mixture

2.1.1 CLASSIFICATION ACCORDING TO REGULATION (EC) NO 1272/2008

Not classified as hazardous according to Classification, Labelling and Packaging regulations (CLP) 1272/2008 EEC

2.2 - Labelling Elements

Not applicable

2.3 - Other hazards which do not result in classification

Mild mechanical irritation to skin, eyes and upper respiratory system may result from exposure.
These effects are usually temporary

3 - Composition / Information On Ingredients

COMPONENTS	CAS NUMBER	% BY WEIGHT
Alumina	1344-28-1	35-50
Water	7732-18-5	20-40
Potassium Alumino Silicate Wool	N/A (EU Index number 650-016-00-2 Annex VI)	10-20
Propylene Glycol	57-55-6	0-5
Amorphous Silica	7631-86-9	5-10

Man-made vitreous silicate fibres of random orientation with alkaline oxide and alkali earth oxides ($\text{Na}_2\text{O} + \text{K}_2\text{O} + \text{CaO} + \text{MgO} + \text{BaO}$) content greater than or equal to 18% by weight and fulfilling one of the Note Q criteria for exoneration from carcinogen classification

4 - First-Aid measures

Skin

Handling of this material may generate mild mechanical temporary skin irritation. If this occurs, rinse affected areas with water and wash gently. Do not rub or scratch exposed skin.

Eyes

In case of eye contact flush abundantly with water; have eye bath available. Do not rub eyes. Seek medical attention if irritation persists.

Nose and Throat

If these become irritated move to a dust free area, drink water and blow nose. Seek medical attention if irritation persists.

If symptoms persist, seek medical advice.

4.2 - Most Important symptoms and effects, both acute and delayed

No symptoms or effects expected either acute or delayed

4.3 - Indication of any immediate medical attention and special treatment required

No special treatment required, if exposure occurs wash exposed areas to avoid irritation.

5 - Fire-fighting measures

5.1 - Extinguishing media

Use extinguishing agent suitable for surrounding combustible materials.

5.2 - Special hazards arising from the substance or mixture

Non-combustible products,

5.3 - Advice for firefighters

Packaging and surrounding materials may be combustible.

6 - Accidental Release Measures

6.1 - Personal precautions, protective equipment and emergency procedures

When material is wet use gloves, boots and rubber protection clothes when cleaning up
Where abnormally high dust concentrations occur, provide workers with appropriate protective equipment as detailed in section 8.

Restrict access to the area to a minimum number of workers required.
Restore the situation to normal as quickly as possible.

6.2 - Environmental precautions

Prevent further dust dispersion for example by damping the materials.
Do not flush spillage to drain and prevent from entering natural watercourses.
Check for local regulations, which may apply

6.3 - Methods and materials for containment and clean up

Pick up large pieces and use a vacuum cleaner fitted with high efficiency filter (HEPA)
If brushes are used, ensure that the area is wetted down first.
Do not use compressed air for clean-up.
Do not allow to be windblown.
Use gloves, boots and rubber protection clothes when cleaning up.
Avoid clean up procedure that could result in water pollution.

6.4 - Reference to other sections

For further information, please refer to sections 7 and 8

7 - Handling and storage

7.1 - Precautions for safe handling

Do not handle wet product with bare hands. The process or processes should be designed to limit the amount of handling. Regular good housekeeping will minimise secondary dispersal.

7.2 - Conditions for safe storage

Store in original packaging in a dry area.
Avoid storage in temperatures lower than +5°C (risk of solidification).
Avoid damaging the packaging.
Use of recyclable plastic drums and plastic films is recommended

7.3 - Specific end use

Please refer to your local Morgan Thermal Ceramics' supplier.

8 - Risk Management Measures / Exposures Controls / Personal Protection

8.1 - Control parameters

Industrial hygiene standards and occupational exposure limits vary between countries and local jurisdictions. Check which exposure levels apply to your facility, and comply with local regulations. If no regulatory dust or other standards apply, a qualified industrial hygienist can assist with a specific workplace evaluation including recommendations for respiratory protection. Examples of exposure limits applying (in November 2014) in different countries are given below:

Country	MMVF	Source
Austria	1 f/ml	Grenzwerteverordnung
Belgium	10 mg/m ³	Valeurs limites d'exposition professionnelle – VLEP/ Grenswaarden voor beroepsmatige blootstelling – GWBB
Czech Republic	1 f/ml	
Denmark	1 f/ml	Grænseværdier for stoffer og materialer
Finland	1 f/ml	Finnish Ministry of Social Affairs and Health
France	1 f/ml	INRS
Germany*	1.25 mg/m ³	TRGS900
Hungary	1 f/ml	EüM-SZCSM rendelet
Ireland	1 f/ml	HAS - Eire
Italy	1 f/ml	
Luxembourg	1 f/ml	Règlement grand-ducal du 30 juillet 2002
Netherlands	1 f/ml	Social and Economic Council of the Netherlands
Norway	0.5 f/ml	Veiledning om administrative normer for forurensning i arbeidsatmosfære
Poland	2 f/ml	Dziennik Ustaw 2010
Spain	1 f/ml	INSHT
Sweden	1 f/ml	Hygieniska gränsvärden och åtgärder mot luftföroreningar
Switzerland	1 f/ml	SUVA
UK	2 f/ml	EH40/2005
GCC	1 f/ml	Abu Dhabi OSHAD
South Africa	5mg/m ³	Regulation 1179 – Hazardous Chemical Substances 2007

Information on monitoring procedures

United Kingdom

MDHS 59 specific for MMVF: "Man-made mineral fibre - Airborne number concentration by phase-contrast light microscopy" and MDHS 14/4 "General methods for sampling and gravimetric analysis of respirable and inhalable dust"

NIOSH

NIOSH 0500 "Particulates not otherwise regulate, total"
NIOSH 0600 "Particulates not otherwise regulate, respirable"
NIOSH 7400 "Asbestos and other fibres by PCM"

8.2 - Exposure controls

8.2.1 APPROPRIATE ENGINEERING CONTROLS

Review your applications in order to identify potential sources of dust exposure.

Local exhaust ventilation, which collects dust at source, can be used. For example down draft tables, emission controlling tools and materials handling equipment. Keep the workplace clean. Use a vacuum cleaner. Avoid brushing and compressed air.

If necessary, consult an industrial hygienist to design workplace controls and practices.

The use of products specially tailored to your application(s) will help to control dust. Some products can be delivered ready for use to avoid further cutting or machining. Some could be pre-treated or packaged to minimise or avoid dust release during handling. Consult your supplier for further details

8.2.2 - Personal Protective Equipment

Skin protection:

Wear gloves and work clothes, which are loose fitting at the neck and wrists. Soiled clothes should be cleaned to remove excess fibres before being taken off (e.g. use vacuum cleaner, not compressed air). Wash work clothes separately from other clothing.

Eye protection:

As necessary wear goggles or safety glasses with side shields.

Respiratory protection:

For dust concentrations below the exposure limit value, RPE is not required but FFP2 respirators may be used on a voluntary basis.

For short-term operations where excursions are less than ten times the limit value use FFP2 respirators.

In case of higher concentrations or where the concentration is not known, please seek advice from your company and/or local Thermal Ceramics supplier.

Information and training of workers

Workers should be trained on good working practices and informed on applicable local regulations.

8.2.3 - Environmental Exposure Controls

Refer to local, national or European applicable environmental standards for release to air water and soil.

For waste, refer to section13

9 - Physical and chemical properties

Information on basic physical and chemical properties	Not Applicable
State	Fibre particulate suspended in liquid form
Colour	Not applicable
Odour	None
Odour threshold	Not Applicable
pH	Not applicable
Melting point/freezing point	> 1200°C
Initial boiling point and boiling point range	Not applicable
Flash point	Not applicable
Evaporation rate	Not Applicable
Flammability (solid, gas)	Not applicable
Upper/lower flammability or explosive limits	Not applicable
Vapour pressure	Not applicable
Vapour density	Not Applicable
Relative density	1 - 2 g/cm ³
Solubility(ies)	Slight
Partition co-efficient: n-octanol/water	Not applicable
Auto-ignition temperature	Not applicable
Decomposition temperature	Not Applicable
Viscosity	Not Applicable
Other safety information	No further relevant information available.
Particle Characteristics	Not applicable
Explosive properties	Not applicable
Oxidising properties	Not applicable

10 - Stability and Reactivity

10.1 - Reactivity

The material is stable and non reactive.

10.2 - Chemical Stability

The product is inorganic, stable and inert

10.3 - Possibility of Hazardous Reactions

None

10.4 - Conditions to Avoid

Please refer to handling and storage advice in Section 7

10.5 - Incompatible Materials

None

10.6 - Hazardous decomposition products

Upon heating above 900°C for sustained periods, this amorphous material begins to transform to mixtures of crystalline phases. For further information please refer to Section 16.

11 - Toxicological information

Toxicokinetics, metabolism and distribution

11.1.1 BASIC TOXICOKINETICS

Exposure is predominantly by inhalation or ingestion. Man made vitreous fibres of a similar size to AES have not been shown to migrate from the lung and/or gut and do not become located in other organs of the body

Fibres contained in the products listed in the title have been designed to be rapidly cleared from lung tissue. This low biopersistence has been confirmed in many studies on AES using EU protocol ECB/TM/27(rev 7). When inhaled, even at very high doses, they do not accumulate to any level capable of producing a serious adverse biological effect.

11.1 - Information on hazard classes as defined in Regulation (EC) No 1272/2008

In lifetime chronic studies there was no exposure-related effect more than would be seen with any "inert" dust. Subchronic studies at the highest doses achievable produced at worst a transient mild inflammatory response. Fibres with the same ability to persist in tissue do not produce tumours when injected into the peritoneal cavity of rats.

Superwool fibres are negative when tested using approved methods (OECD TG 404). Like all man-made mineral fibres and some natural fibres, fibres contained in this product can produce a mild mechanical irritation resulting in temporary itching or rarely, in some sensitive individuals, in a slight temporary reddening. Unlike other irritant reactions this is not the result of allergy or chemical skin damage but is caused by mechanical effects.

12 - Ecological information

12.1 - Toxicity

These products are inert materials that remain stable overtime.
No adverse effects of this material on the environment are anticipated.

12.2 - Persistence and degradability

Not established

12.3 - Bioaccumulative potential

Not established

12.4 - Mobility in soil

No information available

12.5 - Results of PBT and vPvB assessment

This mixture contains no substance considered to be persistent, bioaccumulating nor toxic (PBT).

This mixture contains no substance considered to be very persistent and very bioaccumulative (vPvB).

12.6 - Endocrine Disrupting Properties

No additional information available

12.7 - Other adverse effects

13 - Disposal Considerations

13.1 - Disposal Considerations

To prevent waste materials from becoming airborne during waste storage, transportation and disposal, a covered container or plastic bagging is recommended.

For Australia, waste from these materials should be considered as hazardous waste and local waste authorities should be contacted for correct disposal methods.

For other countries, waste from these materials (even after use above 900°C) is not classified as hazardous waste and may generally be disposed of at a normal tipping site which has been licensed for the disposal of industrial waste. Taking into account any possible contamination during use, which may be classified as hazardous, expert guidance should be sought.

Such a waste is normally dusty (unless wetted) and so should be properly bagged and clearly labelled for disposal. At some tip sites dusty waste may be treated differently in order to ensure they are dealt with promptly and to avoid them being windblown. Check for national and /or regional regulations to identify all applicable disposal requirements.

14 - Transport information

14.1 - Transport information

14.1. UN number

Not Applicable

14.2. UN proper shipping name

Not Applicable

14.3. Transport hazard class(es)

Not Applicable

14.4. Packing group

Not Applicable

14.5. Environmental hazards

Not Applicable

14.6. Special precautions for user

Not Applicable

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not Applicable

15 - Regulatory information

15.1 - Regulatory information

This SDS has been prepared in accordance with WHO GHS rev. 6 requirements. Where applicable, local regulations have been followed.

16 - Other Information

16.1 - ADDITIONAL INFORMATION AND PRECAUTIONS TO BE CONSIDERED UPON REMOVAL OF AFTER SERVICE MATERIAL

ADDITIONAL INFORMATION AND PRECAUTIONS TO BE CONSIDERED UPON REMOVAL OF AFTER SERVICE MATERIAL

As produced, all Refractory Ceramic Fibres are vitreous (glassy) materials which, upon continued exposure to elevated temperatures (above 900°C), may devitrify. The occurrence and extent of crystalline phase formation is dependent on the duration and temperature of exposure, fibre chemistry and/or the presence of fluxing agents. The presence of crystalline phases can be confirmed only through laboratory analysis of the "hot-face" fibre.

IARC's evaluation of crystalline silica states "Crystalline silica inhaled in the form of quartz or cristobalite from occupational sources is carcinogenic to humans (Group 1)" and additionally mentioned "in making the overall evaluation, the Working Group noted that carcinogenicity in humans was not detected in all industrial circumstances studied..."

As only a thin layer of the insulation (hot face side) is exposed to high temperatures, respirable dust generated during removal operations does not contain detectable levels of crystalline silica (CS).

In applications where the material is heat soaked, duration of heat exposure is normally short and a significant devitrification allowing CS to build up does not occur. This is the case for waste mould casting for instance.

Toxicological evaluation of the effect of the presence of CS in artificially heated RCF/ASW material has not shown any increased toxicity in vitro.

The lack of toxicological effects may be explained by the following factors;

Increased brittleness of fibres after service life, favours fast fibre translocation through macrophage.

Microcrystals, including crystalline silica, are embedded in the glass structure of the fibre and are therefore not biologically available. The IARC evaluation as provided in Monograph 68 is not relevant as CS is not biologically available in after- service RCF/ASW.

High concentrations of fibres and other dusts may be generated when after-service products are mechanically disturbed during operations such as wrecking. Therefore MTC recommends:

- a) control measures are taken to reduce dust emissions;
- b) all personnel directly involved wear an appropriate respirator to minimise exposure; and
- c) Compliance with local regulatory limits.

16.2 - uses advised against

16.3 - NOTE

This Safety Data Sheet was originally produced in English and has subsequently been translated in to other languages; whilst every effort has been made to make this an accurate translation, please be aware that technical terms do not always translate correctly. The English version should always be considered as the reference version.

16.4 - Further Information

FURTHER INFORMATION

Further information can be found on

<http://www.morganthermalceramics.com/>

<http://www.cdc.gov/niosh/docs/2006-123/>

<http://www.ecfia.eu/>

http://echa.europa.eu/chem_data/authorisation_process/candidate_list_obligations_en.asp

16.5 - Technical Datasheets

TECHNICAL DATA SHEETS

For more information on individual products please see the technical data sheet section at www.morganthermalceramics.com

16.6 - Revision Summary

New Safety Data Sheet

16.7 - NOTICE

The information presented herein is based on data considered to be accurate as of the date of preparation of this Safety Data Sheet. However, no warranty or representation, express or implied, is made as to the accuracy or completeness of the foregoing data and safety information, nor is any authorization given or implied to practice any patented invention without a license. In addition, no responsibility can be assumed by the vendor for any damage or injury resulting from abnormal use, from any failure to adhere to recommended practices, or from any hazards inherent in the nature of the product.