

SAFETY DATA SHEET

(Following Regulations (EC) No 1907/2006 & (EC) No 1272/2008)

SDS Number: 226 Date of first issue: 01 December 2002 Date of last revision: 21 February 2022

1 - Identification of product

1.1 - Identification of Product

Tradenames: P160, P160K, P161, P161K, P162K, P162SP, P170, P170K,

The above-mentioned products contain polycrystalline wools.

1.2 - Use of Product

Application as thermal insulation, heat shields, heat containment, gaskets and expansion joints at temperatures up to 1600°C in industrial furnaces, ovens, kilns, and other process equipment and in the aerospace, automotive industries.

1.3 - Identification of Company

IDENTIFICATION OF THE MANUFACTURER/SUPPLIER

Morgan Advanced Materials Thermal Ceramics 30-36 Birralee Road, Regency Park, SA 5010, Australia Telephone: 1800 467 858 Fax: 1800 467 850

Website

www.morganthermalceramics.com sds.tc@morganplc.com

1.4 - Emergency information

EMERGENCY CONTACT NUMBER

Tel 1: +91 (4172) 244 313 extn no. 215 or 201 Language: English

Opening hours: Only available during office hours

2 - Hazard Identification

2.1 - Classification of the substance/ mixture

2.1.1 CLASSIFICATION ACCORDING TO REGULATION (EC) NO 1272/2008

Not classified as hazardous according to Classification, Labelling and Packaging regulations (CLP) 1272/2008 EEC

2.2 - Labelling Elements

Not applicable

2.3 - Other hazards which do not result in classification

Mild mechanical irritation to skin, eyes and upper respiratory system may result from exposure. These effects are usually temporary

3 - Composition / Information On Ingredients

These products are boards or forms made of inorganic bound polycrystalline fibres.

COMPONENT	%	CAS Number	Index number	REACH Registration Number
Polycrystalline Fibre	50-85	675106-31-7	Not applicable	Not yet available
Inert inorganic binders	5-20	7631-86-9/12042-91-0	Not applicable	Not yet available
Other mineral material	5-35	Not applicable	Not applicable	Not yet available

None of the components are radioactive under the terms of European Directive Euratom 96/29.

4 - First-Aid measures

Skin

Handling of this material may generate mild mechanical temporary skin irritation. If this occurs, rinse affected areas with water and wash gently. Do not rub or scratch exposed skin.

Eyes

In case of eye contact flush abundantly with water; have eye bath available. Do not rub eyes. Seek medical attention is irritation persists.

Nose and Throat

If these become irritated move to a dust free area, drink water and blow nose. Seek medical attention if irritation persists.

If symptoms persist, seek medical advice.

4.2 - Most Important symptoms and effects, both acute and delayed

4.3 - Indication of any immediate medical attention and special treatment required

5 - Fire-fighting measures

5.1 - Extinguishing media

Non-combustible products. Fire protection class: 0

Packaging and surrounding materials could be combustible.

Use extinguishing agent suitable for surrounding combustible materials.

5.2 - Special hazards arising from the substance or mixture

5.3 - Advice for firefighters

6 - Accidental Release Measures

6.1 - Personal precautions, protective equipment and emergency procedures

Where abnormally high dust concentrations occur, provide the workers with appropriate protective equipment as detailed in section 8. Restore the situation to normal as quickly as possible.

6.2 - Environmental precautions

Prevent further dust dispersion for example by damping the materials. Do not flush spillage to drain and prevent from entering natural watercourses. Check for local regulations, which may apply

6.3 - Methods and materials for containment and clean up

Pick up large pieces and use a vacuum cleaner. If brushes are used, ensure that the area is wetted down first. Do not use compressed air for clean up. Do not allow to become windblown.

6.4 - Reference to other sections

7 - Handling and storage

7.1 - Precautions for safe handling

Handling can be a source of dust emission and therefore the processes should be designed to limit the amount of handling. Whenever possible, handling should be carried out under controlled conditions (i.e., using dust exhaust system). Regular good housekeeping will minimise secondary dust dispersal.

7.2 - Conditions for safe storage

Store in original packaging in a dry area. Always use sealed and clearly labelled containers. Avoid damaging containers. Reduce dust emission during unpacking.

7.3 - Specific end use

The main application of these products is as thermal insulation. Please refer to your local Morgan Thermal Ceramics' supplier.

8 - Risk Management Measures / Exposures Controls / Personal Protection

8.1 - Control parameters

8.1.2 RECOMMENDED MONITORING PROCEDURES

France: Phase contrast optical microscopy test method reference number XP X43-269 dated March 2002, United Kingdom: MDHS 59 specific for MMVF: "Man-made mineral fibre - Airborne number concentration by phase-contrast light microscopy" and MDHS 14/3 "General methods for sampling and gravimetric analysis of respirable and inhalable dust"

Germany TRGS 402 and description of applicable sampling / analytical methods in BGI 505-31 and BGI 505-46.

WHO-EURO method: Determination of airborne fibre number concentrations; A recommended method, by phase-contrast optical microscopy (membrane filter method); World Health Organisation Geneva 1997 ISBN 92 4 154496 1.

Information on monitoring procedures

8.2 - Exposure controls

8.2.1 APPROPRIATE ENGINEERING CONTROLS Review your applications in order to identify potential sources of dust exposure. Local exhaust ventilation, which collects dust at source, can be used. For example down draft tables, emission controlling tools and materials handling equipment. Keep the workplace clean. Use a vacuum cleaner. Avoid brushing and compressed air

If necessary, consult an industrial hygienist to design workplace controls and practices. The use of products specially tailored to your application(s) will help to control dust. Some products can be delivered ready for use to avoid further cutting or machining. Some could be pretreated or packaged to minimise or avoid dust release during handling

Consult your supplier for further details 8.2.2 - Personal Protective Equipment

Skin protection:

Wear gloves and work clothes, which are loose fitting at the neck and wrists. Soiled clothes should be cleaned to remove excess fibres before being taken off (e.g. use vacuum cleaner, not compressed air). Wash work clothes seperately from other clothing.

Eye protection:

As necessary wear goggles or safety glasses with side shields.

Respiratory protection:

For dust concentrations below the exposure limit value, RPE is not required but FFP2 respirators may be used on a voluntary basis. For short-term operations where excursions are less than ten times the limit value use FFP2 respirators. In case of higher concentrations or where the concentration is not known, please seek advice from your company and/or local Thermal Ceramics supplier.

Information and training of workers

Workers should be trained on good working practices and informed on applicable local regulations.

8.2.3 - Environmental Exposure Controls

Refer to local, national or European applicable environmental standards for release to air water and soil. For waste, refer to section13

9 - Physical and chemical properties

Information on basic physical and chemical properties
State
Colour
Odour
Odour threshold
рН
Melting point/freezing point
Initial boiling point and boiling point range
Flash point
Evaporation rate
Flammability (solid, gas)
Upper/lower flammability or explosive limits
Vapour pressure
Vapour density
Relative density
Solubility(ies)
Partition co-efficient: n-octanol/water
Auto-ignition temperature
Decomposition temperature
Viscosity
Other safety information
Particle Characteristics
Explosive properties
Oxidising properties
10 - Stability and Reactivity

Not Applicable White board or form Not appicable Sliaht Not Applicable Not applicable > 1850°C Not applicable 225 - 600 kg/m³ Less than 1 mg/l Not applicable Not applicable Not Applicable Not Applicable No further relevant information available. Not appicable Not applicable Not applicable

10.1 - Reactivity

PCW is stable and non reactive

10.2 - Chemical Stability

The product is inorganic, stable and inert

10.3 - Possibility of Hazardous Reactions

None

10.4 - Conditions to Avoid

Please refer to handling and storage advice in Section 7

10.5 - Incompatible Materials

None

10.6 - Hazardous decomposition products

None

11 - Toxicological information

Toxicokinetics, metabolism and distribution

11.1 Basic toxicokinetics

Exposure is predominantly by inhalation or ingestion. Polycrystalline fibres have not been shown to migrate from the lung and/or gut and do not become located in other organs of the body. Available toxicological information is as follows:

11.1 - Information on hazard classes as defined in Regulation (EC) No 1272/2008

Lifetime rat inhalation studies in the rat on PCW fibres at the maximum levels achievable have shown no evidence of lung cancer, lung fibrosis or any other adverse effect, apart from a minimal pulmonary response typical of that of a 'low toxicity dust'.

Also, a lifetime feeding study in rats has produced no evidence of any adverse effects at levels up to 2.5 % in the diet.

Intraperitoneal, intratracheal and intrapleural studies in rats, together with two in vitro tests, all showed negative results whereas asbestos and crystalline silica which were used as positive controls (where relevant) produced positive responses.

The results of these extensive testing programmes indicate that PCW materials lack one or more of the fundamental characteristics necessary for mesothelioma induction, as well as not possessing fibrogenic potential.

When tested using approved methods (as listed in Regulation (EC) 1907/2006, Annex 8, Section 8.1), fibres contained in this material give negative results. All man-made mineral fibres, like some natural fibres, can produce a mild irritation resulting in itching or rarely, in some sensitive individuals, in a slight reddening. Unlike other irritant reactions this is not the result of allergy or chemical skin damage but is caused by mechanical effects.

12 - Ecological information

12.1 - Toxicity

These products are inert materials that remain stable overtime. No adverse effects of this material on the environment are anticipated.

12.2 - Persistence and degradability

- 12.3 Bioaccumulative potential
- 12.4 Mobility in soil
- 12.5 Results of PBT and vPvB assessment
- 12.6 Endocrine Disrupting Properties
- 12.7 Other adverse effects

13 - Disposal Considerations

13.1 - Disposal Considerations

To prevent waste materials from becoming airborne during waste storage, transportation and disposal, a covered container or plastic bagging is recommended.

For Australia, waste from these materials should be considered as hazardous waste and local waste authorities should be contacted for correct disposal methods.

For other countries, waste from these materials (even after use above 900°C) is not classified as hazardous waste and may generally be disposed of at a normal tipping site which has been licensed for the disposal of industrial waste. Taking into account any possible contamination during use, which may be classified as hazardous, expert guidance should be sought.

Such a waste is normally dusty (unless wetted) and so should be properly bagged and clearly labelled for disposal. At some tip sites dusty waste may be treated differently in order to ensure they are dealt with promptly and to avoid them being windblown. Check for national and /or regional regulations to identify all applicable disposal requirements.

14 - Transport information

14.1 - Transport information

14.1. UN number

Not Applicable

14.2. UN proper shipping name Not Applicable

14.3. Transport hazard class(es) Not Applicable

14.4. Packing group Not Applicable

14.5. Environmental hazards Not Applicable

14.6. Special precautions for user Not Applicable

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not Applicable

15 - Regulatory information

15.1 - Regulatory information

This SDS has been prepared in accordance with WHO GHS rev. 6 requirements. Where applicable, local regulations have been followed.

16 - Other Information

16.1 - ADDITIONAL INFORMATION AND PRECAUTIONS TO BE CONSIDERED UPON REMOVAL OF AFTER SERVICE MATERIAL

16.2 - uses advised against

16.3 - NOTE

This Safety Data Sheet was originally produced in English and has subsequently been translated in to other languages; whilst every effort has been made to make this an accurate translation, please be aware that technical terms do not always translate correctly. The English version should always be considered as the reference version.

16.4 - Further Information

FURTHER INFORMATION Further information can be found on http://www.exfa.eu/ http://www.exfa.eu/ http://www.safeworkaustralia.gov.au/sites/swa/about/publications/pages/workplace-exposure-standards-airborne-contaminants

16.5 - Technical Datasheets

TECHNICAL DATA SHEETS

For more information on individual products please see the technical data sheet section at www.morganthermalceramics.com

16.6 - Revision Summary

Amendments to sections 2, 3, 4, 5, 6, 8, 9, 12, 14, 15 and 16 to comply with new guidelines

16.7 - NOTICE

The information presented herein is based on data considered to be accurate as of the date of preparation of this Safety Data Sheet. However, no warranty or representation, express or implied, is made as to the accuracy or completeness of the foregoing data and safety information, nor is any authorization given or implied to practice any patented invention without a license. In addition, no responsibility can be assumed by the vendor for any damage or injury resulting from abnormal use, from any failure to adhere to recommended practices, or from any hazards inherent in the nature of the product.