

SAFETY DATA SHEET

(Following Regulations (EC) No 1907/2006 & (EC) No 1272/2008)

SDS Number: 424 Date of first issue: 05 February 2013 Date of last revision: 21 February 2022

1 - Identification of product

1.1 - Identification of Product

Tradenames: FireMaster Paper IMG43, FireMaster Paper IMG52,

The above-mentioned products contain mineral wool.

1.2 - Use of Product

Intumescent mat for fire seal applications

1.3 - Identification of Company

IDENTIFICATION OF THE MANUFACTURER/SUPPLIER

Morgan Advanced Materials
Thermal Ceramics
30-36 Birralee Road, Regency Park, SA 5010, Australia
Telephone: 1800 467 858
Fax: 1800 467 850

Website

www.morganthermalceramics.com
sds.tc@morganplc.com

1.4 - Emergency information

EMERGENCY CONTACT NUMBER

Tel 1: +91 (4172) 244 313 extn no. 215 or 201
Language: English

Opening hours: Only available during office hours

2 - Hazard Identification

2.1 - Classification of the substance/ mixture

2.1.1 CLASSIFICATION ACCORDING TO REGULATION (EC) NO 1272/2008

Not classified as hazardous according to Classification, Labelling and Packaging regulations (CLP) 1272/2008 EEC

2.2 - Labelling Elements

Not applicable

2.3 - Other hazards which do not result in classification

Mild mechanical irritation to skin, eyes and upper respiratory system may result from exposure.
These effects are usually temporary

3 - Composition / Information On Ingredients

These products are expanding intumescent paper, available with and without self adhesive backing paper

COMPONENT	%	CAS/EC Number	Classification according to EC 1272/2008	REACH Registration Number
Mineral Wool	20- 50	287922-11-6	Not Classified	Not yet available
Chopped Strand glass fibre	4.5 - 40	65997-17-3	Article - not classified	Not yet available
Exfoliating Graphite	10 - 40	7782-42-5/ 231-999-5	Not Classified	Not yet available
Polymeric Binder and Self adhesive coating	2.5 - 40	Not applicable - Polymer	Not Classified	Not applicable

Man-made vitreous silicate fibres of random orientation with alkaline oxide and alkali earth oxides (Na₂O + K₂O + CaO + MgO + BaO) content greater than or equal to 18% by weight and fulfilling one of the Note Q criteria for exoneration from carcinogen classification

4 - First-Aid measures

Skin

Handling of this material may generate mild mechanical temporary skin irritation. If this occurs, rinse affected areas with water and wash gently. Do not rub or scratch exposed skin.

Eyes

In case of eye contact flush abundantly with water; have eye bath available. Do not rub eyes. Seek medical attention if irritation persists.

Nose and Throat

If these become irritated move to a dust free area, drink water and blow nose. Seek medical attention if irritation persists.

If symptoms persist, seek medical advice.

4.2 - Most Important symptoms and effects, both acute and delayed

No symptoms or effects expected either acute or delayed

4.3 - Indication of any immediate medical attention and special treatment required

No special treatment required, if exposure occurs wash exposed areas to avoid irritation.

5 - Fire-fighting measures

5.1 - Extinguishing media

Use extinguishing agent suitable for surrounding combustible materials.

5.2 - Special hazards arising from the substance or mixture

Non combustible products. However, virgin product binder may burn and produce gases and/or fumes.

5.3 - Advice for firefighters

Packaging and surrounding materials may be combustible.

6 - Accidental Release Measures

6.1 - Personal precautions, protective equipment and emergency procedures

Where abnormally high dust concentrations occur, provide workers with appropriate protective equipment as detailed in section 8.

Restrict access to the area to a minimum number of workers required.

Restore the situation to normal as quickly as possible.

6.2 - Environmental precautions

Prevent further dust dispersion for example by damping the materials.

Do not flush spillage to drain and prevent from entering natural watercourses.

Check for local regulations, which may apply

6.3 - Methods and materials for containment and clean up

Pick up large pieces and use a vacuum cleaner.

If brushes are used, ensure that the area is wetted down first.

Do not use compressed air for clean up.

Do not allow to become windblown.

6.4 - Reference to other sections

For further information, please refer to sections 7 and 8

7 - Handling and storage

7.1 - Precautions for safe handling

Handling can be a source of dust emission and therefore the processes should be designed to limit the amount of handling. Whenever possible, handling should be carried out under controlled conditions (i.e., using dust exhaust system).

Regular good housekeeping will minimise secondary dust dispersal.

7.2 - Conditions for safe storage

Store in original packaging in a dry area.

Always use sealed and clearly labelled containers.

Avoid damaging containers.

Reduce dust emission during unpacking.

7.3 - Specific end use

Please refer to your local Morgan Thermal Ceramics' supplier.

8 - Risk Management Measures / Exposures Controls / Personal Protection

8.1 - Control parameters

Industrial hygiene standards and occupational exposure limits vary between countries and local jurisdictions. Check which exposure levels apply to your facility, and comply with local regulations. If no regulatory dust or other standards apply, a qualified industrial hygienist can assist with a specific workplace evaluation including recommendations for respiratory protection. Examples of exposure limits applying (in November 2014) in different countries are given below:

COUNTRY	Total Dust (mg/m3)	Resp Dust (mg/m3)	MMVF (f/ml)	Fine Carbon Dust [^] (mg/m3)	Source
Austria	10	6	1	No limit	Grenzwerteverordnung
Belgium	10	3	1	3.5	Valeurs limites d'exposition professionnelle – VLEP/ Grenswaarden voor beroepsmatige blootstelling – GWBB
Denmark	10	5	1	3.5	Grænseværdier for stoffer og materialer
Finland	No limit	No limit	1	3.5	Finnish Ministry of Social Affairs and Health
France	10	5	1	3.5	Institut National de Recherche et de Sécurité
Germany*	10	1,25	1	No limit	TRGS 900
Hungary	No limit	No limit	1	No limit	EüM-SZCSM rendelet
Ireland	10	4	1	3.5	HAS – Ireland
Italy	10	3	1	No limit	Uses EU values
Luxembourg	10	6	1	No limit	Agents Chimiques, Cancérigènes Ou Mutagènes Au Travail
Netherlands	10	5	1	No limit	SER
Norway	10	5	0.5	3.5	Veiledning om administrative normer for forurensning i arbeidsatmosfære
Poland	No limit	No limit	2	No limit	Dziennik Ustaw 2010
Spain	10	3	1	3.5	INSHT
Sweden	10	5	1	3	AFS 2005:17
Switzerland	10	6	1	No limit	SUVA - Valeurs limites d'exposition aux postes de travail
UK	10	4	2	3.5	EH40/2005

[^] Where "No limit" is displayed, use the dust limits

Information on monitoring procedures

United Kingdom

MDHS 59 specific for MMVF: "Man-made mineral fibre - Airborne number concentration by phase-contrast light microscopy" and MDHS 14/4 "General methods for sampling and gravimetric analysis of respirable and inhalable dust"

NIOSH

NIOSH 0500 "Particulates not otherwise regulate, total"

NIOSH 0600 "Particulates not otherwise regulate, respirable"

NIOSH 7400 "Asbestos and other fibres by PCM"

8.2 - Exposure controls

8.2.1 APPROPRIATE ENGINEERING CONTROLS

Review your applications in order to identify potential sources of dust exposure.

Local exhaust ventilation, which collects dust at source, can be used. For example down draft tables, emission controlling tools and materials handling equipment.

Keep the workplace clean. Use a vacuum cleaner. Avoid brushing and compressed air.

If necessary, consult an industrial hygienist to design workplace controls and practices.

The use of products specially tailored to your application(s) will help to control dust. Some products can be delivered ready for use to avoid further cutting or machining. Some could be pre-treated or packaged to minimise or avoid dust release during handling.

Consult your supplier for further details

8.2.2 - Personal Protective Equipment

Skin protection:

Wear gloves and work clothes, which are loose fitting at the neck and wrists. Soiled clothes should be cleaned to remove excess fibres before being taken off (e.g. use vacuum cleaner, not compressed air). Wash work clothes separately from other clothing.

Eye protection:

As necessary wear goggles or safety glasses with side shields.

Respiratory protection:

For dust concentrations below the exposure limit value, RPE is not required but FFP2 respirators may be used on a voluntary basis.

For short-term operations where excursions are less than ten times the limit value use FFP2 respirators.

In case of higher concentrations or where the concentration is not known, please seek advice from your company and/or local Thermal Ceramics supplier.

Information and training of workers

Workers should be trained on good working practices and informed on applicable local regulations.

8.2.3 - Environmental Exposure Controls

Refer to local, national or European applicable environmental standards for release to air water and soil.

For waste, refer to section13

9 - Physical and chemical properties

Information on basic physical and chemical properties

State	Not Applicable
Colour	Pale green-grey fibrous paper
Odour	Not applicable
Odour threshold	None
pH	Not Applicable
Melting point/freezing point	Not applicable
Initial boiling point and boiling point range	Not determined
Flash point	Not applicable
Evaporation rate	Not applicable
Flammability (solid, gas)	Not Applicable
Upper/lower flammability or explosive limits	The material will burn for a short period only until the polymeric binder is burnt out or the resulting expansion self-extinguishes
Vapour pressure	Not applicable
Vapour density	Not applicable
Relative density	Not Applicable
Solubility(ies)	Not applicable
Partition co-efficient: n-octanol/water	Not applicable
Auto-ignition temperature	Not applicable
Decomposition temperature	Not Applicable
Viscosity	Not Applicable
Other safety information	No further relevant information available.
Particle Characteristics	Not applicable
Explosive properties	Not applicable
Oxidising properties	Not applicable

10 - Stability and Reactivity

10.1 - Reactivity

The product is stable

10.2 - Chemical Stability

The product is inorganic, stable and inert

10.3 - Possibility of Hazardous Reactions

None

10.4 - Conditions to Avoid

Please refer to handling and storage advice in Section 7

10.5 - Incompatible Materials

Strong oxidising agents, strong alkalis and hydrofluoric acid

10.6 - Hazardous decomposition products

Decomposition of the polymeric binder will occur at temperatures above 200°C releasing smoke, H₂O, CO, CO₂ and hydrocarbons. When heated above 250°C the graphite will expand resulting in a thermally insulating char.

Hazardous Polymerisation: Will not occur.

11 - Toxicological information

Toxicokinetics, metabolism and distribution

11.1.1 BASIC TOXICOKINETICS

Exposure is predominantly by inhalation or ingestion. Man made vitreous fibres of a similar size to Mineral Wool have not been shown to migrate from the lung and/or gut and do not become located in other organs of the body
Fibres contained in the products listed in the title have been designed to be rapidly cleared from lung tissue. When inhaled, even at very high doses, they do not accumulate to any level capable of producing a serious adverse biological effect.

11.1.2 Human Toxicological data

RESPIRATORY TOXICITY FOR MINERAL WOOLS

Epidemiological studies did not show any health effects related to fibres among Mineral Wool manufacturing workers. The excess of lung cancers reported in 1982 have been the subject of additional investigations and the examination of the confounding factors showed that the excess were not attributed to fibres. Smoking has been identified as the most important of these confounding factors.

RESPIRATORY TOXICITY FOR GRAPHITE

Cases of pneumoconiosis, pulmonary fibrosis and emphysema have been reported in workers following prolonged exposures to high levels of airborne graphite dust

11.1 - Information on hazard classes as defined in Regulation (EC) No 1272/2008

Experimental Studies for Mineral Wools

Animal inhalation studies on mineral wools showed neither pulmonary fibrosis nor lung cancer nor mesothelioma. Intratracheal and intraperitoneal injection studies did not show any disease except those involving selected fine glass fibres for special uses or experimental rock wools.

Experimental Studies for Chopped Strand glass fibre

Because of its large diameter, continuous glass filament is not considered to be respirable.

The International Agency for Research on Cancer (IARC) has classified continuous filament glass fibre as not classifiable with respect to human carcinogenicity (Group 3).

In our experience and according to information available to us the product is not harmful to health provided it is correctly handled and processed according to the given recommendations.

Negative results have been obtained in animal studies (EU method B 4) for skin irritation. Inhalation exposures using the nose only route produce simultaneous heavy exposures to the eyes, but no reports of excess eye irritation exist. Animals exposed by inhalation similarly show no evidence of respiratory tract irritation.

Human data confirms that only mechanical irritation, resulting in itching, occurs in humans following exposure to mineral wools

Skin contact with graphite dusts may cause temporary irritation due to mechanical effects: Repeated prolonged exposures may lead to dermatitis.

12 - Ecological information

12.1 - Toxicity

These products are inert materials that remain stable overtime.
No adverse effects of this material on the environment are anticipated.

12.2 - Persistence and degradability

Not established

12.3 - Bioaccumulative potential

Not established

12.4 - Mobility in soil

No information available

12.5 - Results of PBT and vPvB assessment

This mixture contains no substance considered to be persistent, bioaccumulating nor toxic (PBT).

This mixture contains no substance considered to be very persistent and very bioaccumulative (vPvB).

12.6 - Endocrine Disrupting Properties

No additional information available

12.7 - Other adverse effects

13 - Disposal Considerations

13.1 - Disposal Considerations

To prevent waste materials from becoming airborne during waste storage, transportation and disposal, a covered container or plastic bagging is recommended.

For Australia, waste from these materials should be considered as hazardous waste and local waste authorities should be contacted for correct disposal methods.

For other countries, waste from these materials (even after use above 900°C) is not classified as hazardous waste and may generally be disposed of at a normal tipping site which has been licensed for the disposal of industrial waste. Taking into account any possible contamination during use, which may be classified as hazardous, expert guidance should be sought.

Such a waste is normally dusty (unless wetted) and so should be properly bagged and clearly labelled for disposal. At some tip sites dusty waste may be treated differently in order to ensure they are dealt with promptly and to avoid them being windblown. Check for national and /or regional regulations to identify all applicable disposal requirements.

14 - Transport information

14.1 - Transport information

14.1. UN number

Not Applicable

14.2. UN proper shipping name

Not Applicable

14.3. Transport hazard class(es)

Not Applicable

14.4. Packing group

Not Applicable

14.5. Environmental hazards

Not Applicable

14.6. Special precautions for user

Not Applicable

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not Applicable

15 - Regulatory information

15.1 - Regulatory information

This SDS has been prepared in accordance with WHO GHS rev. 6 requirements. Where applicable, local regulations have been followed.

16 - Other Information

16.1 - ADDITIONAL INFORMATION AND PRECAUTIONS TO BE CONSIDERED UPON REMOVAL OF AFTER SERVICE MATERIAL

16.2 - uses advised against

16.3 - NOTE

This Safety Data Sheet was originally produced in English and has subsequently been translated in to other languages; whilst every effort has been made to make this an accurate translation, please be aware that technical terms do not always translate correctly. The English version should always be considered as the reference version.

16.4 - Further Information

FURTHER INFORMATION

Further information can be found on

<http://www.morganthermalceramics.com/>

<http://www.ecfia.eu/>

<http://www.safeworkaustralia.gov.au/sites/swa/about/publications/pages/workplace-exposure-standards-airborne-contaminants>

16.5 - Technical Datasheets

TECHNICAL DATA SHEETS

For more information on individual products please see the technical data sheet section at www.morganthermalceramics.com

16.6 - Revision Summary

Update to section 8.

16.7 - NOTICE

The information presented herein is based on data considered to be accurate as of the date of preparation of this Safety Data Sheet. However, no warranty or representation, express or implied, is made as to the accuracy or completeness of the foregoing data and safety information, nor is any authorization given or implied to practice any patented invention without a license. In addition, no responsibility can be assumed by the vendor for any damage or injury resulting from abnormal use, from any failure to adhere to recommended practices, or from any hazards inherent in the nature of the product.