

## SAFETY DATA SHEET

(Following Regulations (EC) No 1907/2006 & (EC) No 1272/2008)

SDS Number: 2700 Date of first issue: 01 December 2002 Date of last revision: 21 February 2022

### 1 - Identification of product

#### 1.1 - Identification of Product

**Tradenames:** 101 Cement, 131 Cement, 3539 Cement, 913 Fused Alumina Cement, 921 Insulating Powder, 922 Stop Leak Powder, 932 Pure Alumina Powder, 951 Fused Alumina Grog, 952 Fused Alumina Grog, 961 Pure Alumina Cement, C40 Cement, C60 Cement, CB40 Cement, CC60 Cement, Sprout Luting Cement,

The above-mentioned products are dry refractory powders.

#### 1.2 - Use of Product

These products are monolithic refractories used in lining industrial furnaces, high temperature processing, kilns and metal melting applications

#### 1.3 - Identification of Company

**U.K.** THERMAL CERAMICS LIMITED  
Tebay Road, Bromborough  
Wirral, Merseyside CH62 3PH  
Tel. : +44 (0) 151 334 4030  
Fax : +44 (0) 151 334 1684

#### Website

www.morganthermalceramics.com  
sds.tc@morganplc.com

#### 1.4 - Emergency information

Tel: + 44 (0) 7931 963 973  
Language: English  
Opening hours: Only available during office hours

### 2 - Hazard Identification

#### 2.1 - Classification of the substance/ mixture

2.1.1 CLASSIFICATION ACCORDING TO REGULATION (EC) NO 1272/2008

Not classified as hazardous according to Classification, Labelling and Packaging regulations (CLP) 1272/2008 EEC

#### 2.2 - Labelling Elements

Not applicable

#### 2.3 - Other hazards which do not result in classification

Mild mechanical irritation to skin, eyes and upper respiratory system may result from exposure.  
These effects are usually temporary.

#### CHRONIC EFFECTS FOR CRYSTALLINE SILICA

These products may contain minimal amounts of crystalline silica. Prolonged/repeated inhalation of respirable crystalline silica dust may cause delayed lung injury (silicosis). IARC (International Agency for Research on Cancer) states that there is "sufficient evidence in humans for the carcinogenicity of inhaled crystalline silica in the form of quartz or cristobalite from occupational sources to classify crystalline silica as carcinogenic to humans (Group 1)". (Monograph V 68)  
In making the overall evaluation the Working Group noted however that carcinogenicity in humans was not detected in all industrial circumstances studied.

### 3 - Composition / Information On Ingredients

These products are fine granular materials.

COMPONENT	%	CAS Number	Index number	REACH Registration Number
Alumina	0-100	EINECS No. 215-691-6	Not Applicable	Not yet available
Clay	0-20	EINECS No. 310-127-6	Not Applicable	Not yet available
Alumino silicate	0-95	Not Applicable	Not Applicable	Not yet available

None of the components are radioactive under the terms of European Directive Euratom 96/29.

## **4 - First-Aid measures**

### **4.1 - Description of First Aid Measures.**

#### **Skin**

In case of skin irritation rinse affected areas with water and wash gently. Do not rub or scratch exposed skin.

#### **Eyes**

In case of eye contact flush abundantly with water; have eye bath available. Do not rub eyes. Seek medical attention if irritation persists.

#### **Nose and Throat**

If these become irritated move to a dust free area, drink water and blow nose. Seek medical attention if irritation persists.

If symptoms persist, seek medical advice.

### **4.2 - Most Important symptoms and effects, both acute and delayed**

### **4.3 - Indication of any immediate medical attention and special treatment required**

## **5 - Fire-fighting measures**

### **5.1 - Extinguishing media**

Non-combustible products. Fire protection class: 0

Packaging and surrounding materials could be combustible.

Use extinguishing agent suitable for surrounding combustible materials.

### **5.2 - Special hazards arising from the substance or mixture**

### **5.3 - Advice for firefighters**

## **6 - Accidental Release Measures**

### **6.1 - Personal precautions, protective equipment and emergency procedures**

Provide the workers with appropriate protective equipment until the situation is restored to normal (see section 8).

### **6.2 - Environmental precautions**

Prevent further dust dispersion for example by damping the materials.  
Do not flush spillage to drain and prevent from entering natural watercourses.  
Check for local regulations, which may apply

### **6.3 - Methods and materials for containment and clean up**

Pick up large pieces and use a vacuum cleaner.  
If brushes are used, ensure that the area is wetted down first.  
Do not use compressed air for clean up.  
Do not allow to become windblown.

### **6.4 - Reference to other sections**

## **7 - Handling and storage**

### **7.1 - Precautions for safe handling**

Handling can be a source of dust emission and therefore the processes should be designed to limit the amount of handling. Whenever possible, handling should be carried out under controlled conditions (i.e., using dust exhaust system).  
Regular good housekeeping will minimise secondary dust dispersal.

### **7.2 - Conditions for safe storage**

These products should be kept dry and cool, and containers should be re-sealed after use.  
Avoid damaging the packaging.

### **7.3 - Specific end use**

Please refer to your local Morgan Thermal Ceramics' supplier.

## 8 - Risk Management Measures / Exposures Controls / Personal Protection

### 8.1 - Control parameters

Industrial hygiene standards and occupational exposure limits vary between countries and local jurisdictions. Check which exposure levels apply to your facility. If no regulatory dust or other standards apply, a qualified industrial hygienist can assist with a specific workplace evaluation including recommendations for respiratory protection. Examples of exposure limits for respirable dust (in January 2002) are given below:

COUNTRY	Respirable Dust	EXPOSURE LIMIT*			SOURCE
		Crystalline silica	Quartz	Cristobalite	
Germany	3 mg/m <sup>3</sup> or 6 mg/m <sup>3</sup>		0.15 mg/m <sup>3</sup>	0.15 mg/m <sup>3</sup>	TRGS 900,
France	5 mg/m <sup>3</sup>		0.10 mg/m <sup>3</sup>	0.05 mg/m <sup>3</sup>	Décret 97-331 du 10 avril 1997
U.K.	4 mg/m <sup>3</sup>	0.30 mg/m <sup>3</sup>			HSE - EH40

\* Gravimetric concentrations of respirable dust – 8-hour time weighted average.

### Information on monitoring procedures

#### 8.2 - Exposure controls

##### 8.2.1 APPROPRIATE ENGINEERING CONTROLS

Review your applications in order to identify potential sources of dust exposure.

Local exhaust ventilation, which collects dust at source, can be used. For example down draft tables, emission controlling tools and materials handling equipment. Keep the workplace clean. Use a vacuum cleaner. Avoid brushing and compressed air.

If necessary, consult an industrial hygienist to design workplace controls and practices.

The use of products specially tailored to your application(s) will help to control dust. Some products can be delivered ready for use to avoid further cutting or machining. Some could be pre-treated or packaged to minimise or avoid dust release during handling.

Consult your supplier for further details

##### 8.2.2 - Personal Protective Equipment

Skin protection:

Use of gloves and work clothes is recommended.

Soiled clothes should be cleaned before being taken off (e.g. use vacuum cleaning, not compressed air).

Eye protection:

As necessary wear goggles or safety glasses with side shields.

Respiratory protection:

For dust concentrations below the exposure limit value, RPE is not required but FFP2 respirators may be used on a voluntary basis.

For short-term operations where excursions are less than ten times the limit value use FFP2 respirators.

In case of higher concentrations or where the concentration is not known, please seek advice from your company and/or local Thermal Ceramics' supplier.

### INFORMATION AND TRAINING OF WORKERS

Workers should be trained on good working practices and informed on applicable local regulations

#### 8.2.3 - Environmental Exposure Controls

Refer to local, national or European applicable environmental standards for release to air water and soil.

For waste, refer to section13

## 9 - Physical and chemical properties

Information on basic physical and chemical properties	Not applicable
State	White crystals or powders
Colour	Not applicable
Odour	None
Odour threshold	Not applicable
pH	Not applicable
Melting point/freezing point	Not applicable
Initial boiling point and boiling point range	Not applicable
Flash point	Not applicable
Evaporation rate	Not applicable
Flammability (solid, gas)	Not applicable
Upper/lower flammability or explosive limits	Not applicable
Vapour pressure	Not applicable
Vapour density	Not applicable
Relative density	-
Solubility(ies)	Not applicable
Partition co-efficient: n-octanol/water	Not applicable
Auto-ignition temperature	Not applicable
Decomposition temperature	Not applicable
Viscosity	Not applicable
Particle Characteristics	Not applicable
Explosive properties	Not applicable
Oxidising properties	Not applicable

## 10 - Stability and Reactivity

### 10.1 - Reactivity

The material is stable and non reactive.

### 10.2 - Chemical Stability

The product is inorganic, stable and inert

### 10.3 - Possibility of Hazardous Reactions

None

### 10.4 - Conditions to Avoid

Please refer to handling and storage advice in Section 7

### 10.5 - Incompatible Materials

None

### 10.6 - Hazardous decomposition products

None

## 11 - Toxicological information

### Toxicokinetics, metabolism and distribution

#### 11.1.1 BASIC TOXICOKINETICS

As manufactured, these products may contain a minimal amount of crystalline silica.

Exposure is not expected during normal use due to nature of the products, exposure during removal may be possible, predominantly by inhalation or ingestion, available toxicological information is as follows:

#### 11.1.2 Human Toxicological data

Epidemiology for crystalline silica

Prolonged/repeated inhalation of respirable crystalline silica dust may cause delayed lung injury (silicosis).

In evaluating crystalline silica as a cancer risk, the International Agency for Research on Cancer (IARC) reviewed several studies from different industries and concluded that crystalline silica from occupational sources inhaled in the form of quartz or cristobalite is carcinogenic to humans (Group 1) [IARC Monograph; vol.68; June 1997]. However, in reaching its conclusion, IARC stated that the carcinogenicity in humans could not be found in all industries reviewed and that carcinogenicity might be dependent on inherent characteristics of crystalline silica or on external factors affecting biological activity (e.g., cigarette smoking) or distribution of its polymorphs.

#### 11.1 - Information on hazard classes as defined in Regulation (EC) No 1272/2008

Experimental studies for crystalline silica

Animals exposed to very high concentrations of crystalline silica, artificially or by inhalation, have reported fibrosis and tumours (IARC Monographs 42 and 68).

Inhalation and intratracheal installation of crystalline silica in rats caused lung cancer. However, studies in other species such as mice and hamsters caused no lung cancer. Crystalline silica also caused fibrosis in rats and hamsters in several inhalation and intratracheal installation studies.

#### ACUTE TOXICITY

Lethal dose 50 % (LD50) / lethal concentration 50% (LC50): N.A.

## 12 - Ecological information

### 12.1 - Toxicity

These products are inert materials that remain stable overtime.  
No adverse effects of this material on the environment are anticipated.

### 12.2 - Persistence and degradability

### 12.3 - Bioaccumulative potential

### 12.4 - Mobility in soil

### 12.5 - Results of PBT and vPvB assessment

### 12.6 - Endocrine Disrupting Properties

### 12.7 - Other adverse effects

### 13 - Disposal Considerations

Waste from these materials may be generally disposed off at a landfill, which has been licensed for this purpose. Please refer to the European list (Decision N° 2000/532/CE as modified) to identify your appropriate waste number, and insure national and/or regional regulations are complied with.

Unless wetted, such a waste is normally dusty and so should be properly sealed in containers for disposal. At some authorised disposal sites, dusty waste may be treated differently in order to ensure they are dealt with promptly to avoid them being windblown. Check for any national and/or regional regulations, which may apply.

### 14 - Transport information

Not classified as dangerous goods under relevant international transport regulations (ADR, RID, IATA, IMDG).  
Ensure that dust is not windblown during transportation.

Definitions:

ADR Transport by road, council directive 94/55/EC  
IMDG Regulations relating to transport by sea  
RID Transport by rail, Council Directive 96/49/EC  
ICAO/IATA Regulations relating to transport by air  
ADN European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

### 15 - Regulatory information

#### 15.1 - Safety health and environment regulations/legislation specific for the substances or mixtures

EU regulations:

- Regulation (EC) No 1907/2006 dated 18th December 2006 on Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)
- Regulation (EC) No 1272/2008 dated 20th January 2009 on classification, labelling and packaging of substances and mixtures (OJ L 353)
- Annex of Regulation (EU) 2015/830
- Commission regulation (EC) No 790/2009 of 10 August 2009 amending, for the purposes of its adaptation to technical and scientific progress, Regulation (EC) No 1272/2008 of the European Parliament and of the Council on classification, labelling and packaging of substances and mixtures.
- The 1st Adaptation to Technical Progress (ATP) to Regulation (EC) No 1272/2008 enters into force on 25 September 2009.

#### PROTECTION OF WORKERS

Shall be in accordance with several European Directives as amended and their implementations by the Member States:

- a) Council Directive 89/391/EEC dated 12 June 1989 "on the introduction of measures to encourage improvements in the safety and health of workers at work" (OJEC (Official Journal of the European Community) L 183 of 29 June 1989, p.1).
- b) Council Directive 98/24/EC dated 7 April 1998 "on the protection of workers from the risks related to chemical agents at work" (OJEC L 131 of 5 May 1998, p.11).

#### OTHER POSSIBLE REGULATIONS

Member States are in charge of implementing European Directives into their own national regulation within a period of time normally given in the Directive. Member States may impose more stringent requirements. Please always refer to any national regulation.

#### 15.2 - Chemical Safety Assessment

Chemical Safety Reports have been requested from suppliers, as soon as this information is available it will be shared with downstream users.

### 16 - Other Information

(the directives which are cited must be considered in their amended version)

- Council Directive 89/391/EEC dated 12 June 1989 "on the introduction of measures to encourage improvements in the safety and health of workers at work" (OJEC L 183 of 29 June 1989, p.1).
- Regulation (EC) No 1907/2006 dated 18th December 2006 on registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)
- Regulation (EC) No 1272/2008 dated 20th January 2009 on classification, labelling and packaging of substances and mixtures (OJ L 353)
- Council Directive 98/24/EC of 7 April 1998 "on the protection of the health and safety of workers from the risks related to chemical agents at work" (OJEC L 131 of 5 May 1998, p11).

Additional information and precautions to be considered upon removal of after service material

Continuous use of these products at temperatures above 900°C may, as with many other refractories, lead to the formation of cristobalite (a type of crystalline silica).  
Please refer to sections 2, 11 and to national regulation on crystalline silica.

High concentrations of dusts may be generated when after-service products are mechanically disturbed during operations such as wrecking. Therefore Morgan Thermal Ceramics recommends:

- a) control measures are taken to reduce dust emissions;
- b) all personnel directly involved wear an appropriate respirator to minimise exposure; and
- c) Compliance with local regulatory limits.

For more information connect to:

The Morgan Thermal Ceramics' website: (<http://www.morganthermalceramics.com/>)

Or ECFIA's website: (<http://www.ecfia.eu>)

#### Revision Summary

General Update of SDS to comply with REACH Regulation, changes to sections 1-16

#### Technical data sheets

For more information on individual products please see the relevant technical data sheet available from <http://www.morganthermalceramics.com/downloads/datasheets>

#### NOTICE:

The information presented herein is based on data considered to be accurate as of the date of preparation of this Material Safety Data Sheet. However safe as provided by law, no warranty or representation, express or implied, is made as to the accuracy or completeness of the foregoing data and safety information, nor is any authorisation given or implied to practice any patented invention without a licence. In addition, no responsibility can be assumed by the vendor for any damage or injury resulting from abnormal use, from any failure to adhere to recommended practices, or from any hazards inherent in the nature of the product (however, this shall not act to restrict the vendor's potential liability for negligence or under statute).