

SAFETY DATA SHEET

(Following Regulations (EC) No 1907/2006 & (EC) No 1272/2008)

SDS Number: 504 Date of first issue: 01 November 2009 Date of last revision: 21 February 2022

1 - Identification of product

1.1 - Identification of Product

Tradenames: K25 Brick, TJM20, TJM23, TJM25, TJM25HS, TJMB4, TJMB5, TJMC1,

The above-mentioned products are insulating firebricks and are considered articles without intended release for the purposes of REACH.

1.2 - Use of Product

Application as high temperature processing, lining of industrial furnaces, thermal insulation of kilns, etc... (Please refer to specific technical data sheet for more information).

1.3 - Identification of Company

IDENTIFICATION OF THE MANUFACTURER/SUPPLIER

Morgan Advanced Materials Thermal Ceramics 30-36 Birralee Road, Regency Park, SA 5010, Australia Telephone: 1800 467 858 Fax: 1800 467 850

Website

www.morganthermalceramics.com sds.tc@morganplc.com

1.4 - Emergency information

Tel: 1800 467 858 Language: English Opening hours: Monday to Friday 08:30 to 16:30

2 - Hazard Identification

2.1 - Classification of the substance/ mixture

Classified as hazardous according to the criteria of Safework Australia as a category 1a Carcinogen Not classified as a dangerous good according to the criteria of the ADG Code

2.2 - Labelling Elements

Component	Classification	Hazard pictogram & Symbol	H Statement
Crystalline Silica	Safework Australia	GHS 08	H350I

Hazard pictogram	GHS 08	
Signal Word	Danger	
Hazard Statements	May cause cancer by inhalation (H350i)	
Precautionary statements	Do not handle until all safety instructions have been read and understood. (P202) Use personal protective equipment as required. (P281)	

2.3 - Other hazards which do not result in classification

Mild mechanical irritation to skin, eyes and upper respiratory system may result from exposure. These effects are usually temporary.

CHRONIC EFFECTS FOR CRYSTALLINE SILICA

These products may contain minimal amounts of crystalline silica. Prolonged/repeated inhalation of respirable crystalline silica dust may cause delayed lung injury (silicosis).

IARC (International Agency for Research on Cancer) states that there is "sufficient evidence in humans for the carcinogenicity of inhaled crystalline silica in the form of quartz or cristobalite from occupational sources to classify crystalline silica as carcinogenic to humans (Group 1)". (Monograph V 68) In making the overall evaluation the Working Group noted however that carcinogenicity in humans was not detected in all industrial circumstances studied.

3 - Composition / Information On Ingredients

3.2 Mixture

These products are beige porous insulating firebricks.

Component	% by weight	CAS No.	REACH Registration Number	Hazard Classification according to CLP
Crystalline Silica	>2.5	14808-60-7	Not yet availiable	STOT RE1
Aluminium Oxide	1-5	1344-28-1	01-2119817795-27	Not classified
Alumino silicate	40-70	EINECS: 235-253-8	Not yet availiable	Not classified
Other inert material	10-30	Not Applicable	Not yet availiable	Not classified

None of the components are radioactive under the terms of European Directive Euratom 96/29.

4 - First-Aid measures

Skin

In case of skin irritation rinse affected areas with water and wash gently. Do not rub or scratch exposed skin.

Eyes

In case of eye contact flush abundantly with water; have eye bath available. Do not rub eyes. Seek medical attention is irritation persists.

Nose and Throat

If these become irritated move to a dust free area, drink water and blow nose. Seek medical attention if irritation persists.

If symptoms persist, seek medical advice.

4.2 - Most Important symptoms and effects, both acute and delayed

No symptoms or effects expected either acute or delayed

4.3 - Indication of any immediate medical attention and special treatment required

No special treatment required, if exposure occurs wash exposed areas to avoid irritation.

5 - Fire-fighting measures

5.1 - Extinguishing media

Use extinguishing agent suitable for surrounding combustible materials.

5.2 - Special hazards arising from the substance or mixture

Non-combustible products,

5.3 - Advice for firefighters

Packaging and surrounding materials may be combustible.

6 - Accidental Release Measures

6.1 - Personal precautions, protective equipment and emergency procedures

Provide the workers with appropriate protective equipment until the situation is restored to normal (see section 8).

6.2 - Environmental precautions

Prevent further dust dispersion for example by damping the materials. Do not flush spillage to drain and prevent from entering natural watercourses. Check for local regulations, which may apply

6.3 - Methods and materials for containment and clean up

Pick up large pieces and use a vacuum cleaner. If brushes are used, ensure that the area is wetted down first. Do not use compressed air for clean up. Do not allow to become windblown.

6.4 - Reference to other sections

For further information, please refer to sections 7 and 8

7 - Handling and storage

7.1 - Precautions for safe handling

Handling can be a source of dust emission and therefore the processes should be designed to limit the amount of handling. Whenever possible, handling should be carried out under controlled conditions (i.e., using dust exhaust system). Regular good housekeeping will minimise secondary dust dispersal.

7.2 - Conditions for safe storage

Store in original packaging in dry area whilst awaiting use Avoid damaging packaging. Recyclable cardboard and/or plastic films are recommended for packaging.

7.3 - Specific end use

Please refer to your local Morgan Thermal Ceramics' supplier.

8 - Risk Management Measures / Exposures Controls / Personal Protection

8.1 - Control parameters

Removing dried material after use may generate respirable dust.

Industrial hygiene standards and occupational exposure limits vary between countries and local jurisdictions. Check which exposure levels apply to your facility and comply with local regulations. If no regulatory dust or other standards apply, a qualified industrial hygienist can assist with a specific workplace evaluation including recommendations for respiratory protection.

Examples of national OELs (October 2021) are given in the table below. Additional references and/or updates can be found on the following websites:

http://www.dguv.de/ifa/en/gestis/limit_values

http://osha.europa.eu/en/publications/reports/548OELs/view

COUNTRY	Total Dust (mg/m3)	Resp Dust (mg/m3)	Quartz (mg/m3)	Cristobalite (mg/m3)	Source
India					Directorate General Factory Advice Service & Labour Industries (DFGASLI)
China					GBZ 2.1-2019
Japan					The Japan Society for Occupational Health (JSOH)
Korea					K-OSHA Value
UAE					Abu Dhabi Occupational Safety and Health System Framework (OSHAD-SF) v 3.0 July 2016
Australia	10		0.05	0.05	Workplace Exposure Standards for Airbourne Contaminants, Dec 2019

Information on monitoring procedures

United Kingdom

MDHS 14/4 - "General methods for sampling and gravimetric analysis of respirable, thoracic and inhalable aerosols"

MDHS 101 - "Crystalline silica in respirable airborne dusts"

NIOSH

NIOSH 0500 "Particulates not otherwise regulated, total" NIOSH 0600 "Particulates not otherwise regulated, respirable" NIOSH 7500 " Silica, Crystalline, by XRD (filter redeposition)"

8.2 - Exposure controls

8.2.1 APPROPRIATE ENGINEERING CONTROLS

Review your applications in order to identify potential sources of dust exposure.

Local exhaust ventilation, which collects dust at source, can be used. For example down draft tables, emission controlling tools and materials handling equipment. Keep the workplace clean. Use a vacuum cleaner. Avoid brushing and compressed air.

If necessary, consult an industrial hygienist to design workplace controls and practices. The use of products specially tailored to your application(s) will help to control dust. Some products can be delivered ready for use to avoid further cutting or machining. Some could be pretreated or packaged to minimise or avoid dust release during handling.

Consult your supplier for further details

8.2.2 - Personal Protective Equipment

Skin protection:

Use of gloves and work clothes is recommended.

Soiled clothes should be cleaned before being taken off (e.g. use vacuum cleaning, not compressed air).

Eve protection:

As necessary wear goggles or safety glasses with side shields.

Respiratory protection:

For dust concentrations below the exposure limit value, RPE is not required but FFP2 respirators may be used on a voluntary basis.

For short-term operations where excursions are less than ten times the limit value use FFP2 respirators.

In case of higher concentrations or where the concentration is not known, please seek advice from your company and/or local Thermal Ceramics' supplier.

INFORMATION AND TRAINING OF WORKERS

Workers should be trained on good working practices and informed on applicable local regulations

8.2.3 - Environmental Exposure Controls

Refer to local, national or European applicable environmental standards for release to air water and soil. For waste, refer to section13

9 - Physical and chemical properties

Inf Sta	ormation on basic physical and chemical properties
	lour
	lour
	our threshold
pH	
	Iting point/freezing point
	tial boiling point and boiling point range
	sh point
Ev	aporation rate
Fla	immability (solid, gas)
Up	per/lower flammability or explosive limits
Va	pour pressure
Va	pour density
Re	lative density
So	lubility(ies)
Ра	rtition co-efficient: n-octanol/water
Au	to-ignition temperature
De	composition temperature
Vis	cosity
Ot	her safety information
Ра	rticle Characteristics
Ex	plosive properties
	idising properties
	- Stability and Reactivity
10	- Stability and Reactivity

Beige porous brick Not appicable None Not Applicable Not applicable > 1700°C Not applicable 0.5 - 1.8 g/cm³ Not applicable Not applicable Not applicable Not Applicable Not Applicable No further relevant information available. Not appicable Not applicable Not applicable

Not Applicable

10.1 - Reactivity

The material is stable and non reactive.

10.2 - Chemical Stability

The product is inorganic, stable and inert

10.3 - Possibility of Hazardous Reactions

None

10.4 - Conditions to Avoid

Please refer to handling and storage advice in Section 7

10.5 - Incompatible Materials

None

10.6 - Hazardous decomposition products

Upon heating above 900°C for sustained periods, this amorphous material begins to transform to mixtures of crystalline phases. For further information please refer to Section 16.

11 - Toxicological information

Toxicokinetics, metabolism and distribution

11.1.1 BASIC TOXICOKINETICS As manufactured, these products may contain a minimal amount of crystalline silica. Exposure is predominantly by inhalation or ingestion, available toxicological information is as follows:

11.1.2 Human Toxicological data Epidemiology for crystalline silica

Prolonged/repeated inhalation of respirable crystalline silica dust may cause delayed lung injury (silicosis). In evaluating crystalline silica as a cancer risk, the International Agency for Research on Cancer (IARC) reviewed several studies from different industries and concluded that crystalline silica from occupational sources inhaled in the form of quartz or cristobalite is carcinogenic to humans (Group 1) [IARC Monograph; vol.68; June 1997]. However, in reaching its conclusion, IARC stated that the carcinogenicity in humans could not be found in all industries reviewed and that carcinogenicity might be dependent on inherent characteristics of crystalline silica or on external factors affecting biological activity (e.g., cigarette smoking) or distribution of its polymorphs.

11.1 - Information on hazard classes as defined in Regulation (EC) No 1272/2008

Experimental studies for crystalline silica

Animals exposed to very high concentrations of crystalline silica, artificially or by inhalation, have reported fibrosis and tumours (IARC Monographs 42 and 68). Inhalation and intratracheal installation of crystalline silica in rats caused lung cancer. However, studies in other species such as mice and hamsters caused no lung cancer. Crystalline silica also caused fibrosis in rats and hamsters in several inhalation and intratracheal installation studies.

ACUTE TOXICITY Lethal dose 50 % (LD50) / lethal concentration 50% (LC50): N.A.

12 - Ecological information

12.1 - Toxicity

These products are inert materials that remain stable overtime.

No adverse effects of this material on the environment are anticipated.

12.2 - Persistence and degradability

Not established

12.3 - Bioaccumulative potential

Not established

12.4 - Mobility in soil

No information available

12.5 - Results of PBT and vPvB assessment

This mixture contains no substance considered to be persistent, bioaccumulating nor toxic (PBT).

This mixture contains no substance considered to be very persistent and very bioaccumulative (vPvB).

12.6 - Endocrine Disrupting Properties

No additional information available

12.7 - Other adverse effects

13 - Disposal Considerations

13.1 - Disposal Considerations

To prevent waste materials from becoming airborne during waste storage, transportation and disposal, a covered container or plastic bagging is recommended.

For Australia, waste from these materials should be considered as hazardous waste and local waste authorities should be contacted for correct disposal methods.

For other countries, waste from these materials (even after use above 900°C) is not classified as hazardous waste and may generally be disposed of at a normal tipping site which has been licensed for the disposal of industrial waste. Taking into account any possible contamination during use, which may be classified as hazardous, expert guidance should be sought.

Such a waste is normally dusty (unless wetted) and so should be properly bagged and clearly labelled for disposal. At some tip sites dusty waste may be treated differently in order to ensure they are dealt with promptly and to avoid them being windblown. Check for national and /or regional regulations to identify all applicable disposal requirements.

14 - Transport information

14.1 - Transport information

14.1. UN number Not Applicable

14.2. UN proper shipping name Not Applicable

14.3. Transport hazard class(es) Not Applicable

14.4. Packing group Not Applicable

14.5. Environmental hazards Not Applicable

14.6. Special precautions for user Not Applicable

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not Applicable

15 - Regulatory information

15.1 - Regulatory information

This SDS has been prepared in accordance with WHO GHS rev. 6 requirements. Where applicable, local regulations have been followed.

16 - Other Information

16.1 - ADDITIONAL INFORMATION AND PRECAUTIONS TO BE CONSIDERED UPON REMOVAL OF AFTER SERVICE MATERIAL

16.2 - uses advised against

16.3 - NOTE

This Safety Data Sheet was originally produced in English and has subsequently been translated in to other languages; whilst every effort has been made to make this an accurate translation, please be aware that technical terms do not always translate correctly. The English version should always be considered as the reference version.

16.4 - Further Information

FURTHER INFORMATION Further information can be found on http://www.morganthermalceramics.com/ http://www.sedfa.eu/ http://www.safeworkaustralia.gov.au/sites/swa/about/publications/pages/workplace-exposure-standards-airborne-contaminants

16.5 - Technical Datasheets

TECHNICAL DATA SHEETS

For more information on individual products please see the technical data sheet section at www.morganthermalceramics.com

16.6 - Revision Summary

Content checked and revision date updated

16.7 - NOTICE

The information presented herein is based on data considered to be accurate as of the date of preparation of this Safety Data Sheet. However, no warranty or representation, express or implied, is made as to the accuracy or completeness of the foregoing data and safety information, nor is any authorization given or implied to practice any patented invention without a license. In addition, no responsibility can be assumed by the vendor for any damage or injury resulting from abnormal use, from any failure to adhere to recommended practices, or from any hazards inherent in the nature of the product.