

SAFETY DATA SHEET

(Following Regulations (EC) No 1907/2006 & (EC) No 1272/2008)

SDS Number: 1017 Date of first issue: 08 March 2013 Date of last revision: 21 February 2022

1 - Identification of product

1.1 - Identification of Product

Tradenames: FireMaster Putty, Superwool HT Sealcoat,

The above-mentioned products contain Alkaline-earth silicate wools (AES wools)

Index Number: 650-016-00-2 Annex VI

CAS number: 436083-99-7

Registration number: 01-2119457644-32-0000

1.2 - Use of Product

Application as thermal insulation, heat shields, heat containment, gaskets and expansion joints in industrial furnaces, ovens, kilns, boilers and other process. equipment and in the aerospace, automotive and appliance industries, and as passive fire protection systems and fire stops. (Please refer to specific technical data sheet for more information)

1.3 - Identification of Company

IDENTIFICATION OF THE MANUFACTURER/SUPPLIER

Morgan Advanced Materials
Thermal Ceramics
30-36 Birralee Road, Regency Park, SA 5010, Australia
Telephone: 1800 467 858
Fax: 1800 467 850

Website

www.morganthermalceramics.com
sds.tc@morganplc.com

1.4 - Emergency information

EMERGENCY CONTACT NUMBER

Tel 1: +91 (4172) 244 313 extn no. 215 or 201
Language: English

Opening hours: Only available during office hours

2 - Hazard Identification

2.1 - Classification of the substance/ mixture

2.1.1 CLASSIFICATION ACCORDING TO REGULATION (EC) NO 1272/2008

Not classified as hazardous according to Classification, Labelling and Packaging regulations (CLP) 1272/2008 EEC

2.2 - Labelling Elements

Not applicable

2.3 - Other hazards which do not result in classification

Mild mechanical irritation to skin, eyes and upper respiratory system may result from exposure.
These effects are usually temporary

3 - Composition / Information On Ingredients

3.2 Mixture

This product is mastic made of AES wool. Once dried out, this product may generate dust.

| Component | % by weight | CAS No. | REACH Registration Number | Hazard Classification according to CLP |
|--|-------------|--------------------------|---------------------------|--|
| Water | 50-60 | 7732-18-5 | Not applicable | Non hazardous |
| Fused Silica | 10-30 | Not applicable | Not applicable | Non hazardous |
| AES wool (synthetic fibres, alk. earth silicate) | 10-30 | 436083-99-7 | 01-2119457644-32 | Note Q exonerated |
| Clay | <10 | Not applicable | Not applicable | Non hazardous |
| Polymer additive | <1% | Not applicable (polymer) | Not applicable | H412 |
| Preservative | <1% | 51200-87-4 | Not applicable | H302+H332, H226, H315, H318 |

Composition:

* CAS definition: Alkaline earth silicate (AES) consisting of silica (50-82 wt%), calcia and magnesia (18-43 wt%), alumina, titania and zirconia (less than 6 wt%), and trace oxides.

IT IS STATED that these fibres comply with the TERMS of the "NOTE Q" of EUROPEAN COMMISSION regulation EC1272/2008 of 16 December 2008

None of the components are radioactive under the terms of European Directive Euratom 96/29.

4 - First-Aid measures

Skin

In case of skin irritation rinse affected areas with water and wash gently. Do not rub or scratch exposed skin.

Eyes

In case of eye contact flush abundantly with water; have eye bath available. Do not rub eyes. Seek medical attention if irritation persists.

Nose and Throat

If these become irritated move to a dust free area, drink water and blow nose. Seek medical attention if irritation persists.

If symptoms persist, seek medical advice.

4.2 - Most Important symptoms and effects, both acute and delayed

No symptoms or effects expected either acute or delayed

4.3 - Indication of any immediate medical attention and special treatment required

No special treatment required, if exposure occurs wash exposed areas to avoid irritation.

5 - Fire-fighting measures

5.1 - Extinguishing media

Use extinguishing agent suitable for surrounding combustible materials.

5.2 - Special hazards arising from the substance or mixture

Non-combustible products,

5.3 - Advice for firefighters

Packaging and surrounding materials may be combustible.

6 - Accidental Release Measures

6.1 - Personal precautions, protective equipment and emergency procedures

When material is wet use gloves, boots and rubber protection clothes when cleaning up
Where abnormally high dust concentrations occur, provide workers with appropriate protective equipment as detailed in section 8.

Restrict access to the area to a minimum number of workers required.
Restore the situation to normal as quickly as possible

6.2 - Environmental precautions

Do not flush spillage to drain and prevent from entering natural watercourses.
For waste disposal refer to section 13

6.3 - Methods and materials for containment and clean up

Pick up large pieces and use a vacuum cleaner fitted with high efficiency filter (HEPA)
If brushes are used, ensure that the area is wetted down first.
Do not use compressed air for clean-up.
Do not allow to be windblown.
Use gloves, boots and rubber protection clothes when cleaning up.
Avoid clean up procedure that could result in water pollution.

6.4 - Reference to other sections

For further information, please refer to sections 7 and 8

7 - Handling and storage

7.1 - Precautions for safe handling

Do not handle wet product with bare hands. Handling of dried products can be a source of dust emission and therefore the processes should be designed to limit the amount of handling.
Whenever possible, handling should be carried out under controlled conditions (i.e., using dust exhaust system).
Regular good housekeeping will minimise secondary dust dispersal.

7.2 - Conditions for safe storage

Store in original packaging in a dry area.
Avoid storage in temperatures lower than +5°C (risk of solidification).
Avoid damaging the packaging.
Use of recyclable plastic drums and plastic films is recommended

7.3 - Specific end use

Please refer to your local Morgan Thermal Ceramics' supplier.

8 - Risk Management Measures / Exposures Controls / Personal Protection

8.1 - Control parameters

Industrial hygiene standards and occupational exposure limits vary between countries and local jurisdictions. Check which exposure levels apply to your facility and comply with local regulations. If no regulatory dust or other standards apply, a qualified industrial hygienist can assist with a specific workplace evaluation including recommendations for respiratory protection. Examples of national OELs (November 2014) are given in the table below.

| COUNTRY | Total Dust (mg/m ³) | Resp Dust (mg/m ³) | MMMF (fibre/ml) | Source |
|-------------|---------------------------------|--------------------------------|-----------------|---|
| Austria | 10 | 6 | 1 | Grenzwerteverordnung |
| Belgium | 10 | 3 | 1 | Valeurs limites d'exposition professionnelle – VLEP/ Grenswaarden voor beroepsmatige blootstelling – GWBB |
| Denmark | 10 | 5 | 1 | Grænseværdier for stoffer og materialer |
| Finland | No limit | No limit | 1 | Finnish Ministry of Social Affairs and Health |
| France | 10 | 5 | 1 | Institut National de Recherche et de Sécurité |
| Germany | 10 | 1.25 | No Limit | TRGS 900 |
| Hungary | No limit | No limit | 7 | EüM-SZCSM rendelet |
| Ireland | 10 | 4 | 1 | HAS – Ireland |
| Italy | 10 | 3 | 1 | Uses EU values |
| Luxembourg | 10 | 6 | 1 | Agents Chimiques, Cancérigènes Ou Mutagènes Au Travail |
| Netherlands | 10 | 5 | 1 | SER |
| Norway | 10 | 5 | 0.5 | Veiledning om administrative normer for forurensning i arbeidsatmosfære |
| Poland | No limit | No limit | 2 | Dziennik Ustaw 2010 |
| Spain | 10 | 3 | 1 | INSHT |
| Sweden | 10 | 5 | 1 | AFS 2005:17 |
| Switzerland | 10 | 6 | 1 | SUVA - Valeurs limites d'exposition aux postes de travail |
| UK | 10 | 4 | 2 | EH40/2005 |

Information on monitoring procedures

United Kingdom

MDHS 59 specific for MMVF: "Man-made mineral fibre - Airborne number concentration by phase-contrast light microscopy" and MDHS 14/4 "General methods for sampling and gravimetric analysis of respirable and inhalable dust"

NIOSH

NIOSH 0500 "Particulates not otherwise regulate, total"

NIOSH 0600 "Particulates not otherwise regulate, respirable"

NIOSH 7400 "Asbestos and other fibres by PCM"

8.2 - Exposure controls

8.2.1 APPROPRIATE ENGINEERING CONTROLS

Review your applications in order to identify potential sources of dust exposure.

Local exhaust ventilation, which collects dust at source, can be used. For example down draft tables, emission controlling tools and materials handling equipment.

Keep the workplace clean. Use a vacuum cleaner. Avoid brushing and compressed air.

If necessary, consult an industrial hygienist to design workplace controls and practices.

The use of products specially tailored to your application(s) will help to control dust. Some products can be delivered ready for use to avoid further cutting or machining. Some could be pre-treated or packaged to minimise or avoid dust release during handling.

Consult your supplier for further details

8.2.2 - Personal Protective Equipment

Skin protection:

Wear gloves and work clothes, which are loose fitting at the neck and wrists. Soiled clothes should be cleaned to remove excess fibres before being taken off (e.g. use vacuum cleaner, not compressed air). Wash work clothes separately from other clothing.

Eye protection:

As necessary wear goggles or safety glasses with side shields.

Respiratory protection:

For dust concentrations below the exposure limit value, RPE is not required but FFP2 respirators may be used on a voluntary basis.

For short-term operations where excursions are less than ten times the limit value use FFP2 respirators.

In case of higher concentrations or where the concentration is not known, please seek advice from your company and/or local Thermal Ceramics supplier.

Information and training of workers

Workers should be trained on good working practices and informed on applicable local regulations.

8.2.3 - Environmental Exposure Controls

Refer to local, national or European applicable environmental standards for release to air water and soil.

For waste, refer to section13

9 - Physical and chemical properties

| | |
|--|--|
| Information on basic physical and chemical properties | Not Applicable |
| State | Fibre particulate suspended in liquid form |
| Colour | Not applicable |
| Odour | None |
| Odour threshold | Not Applicable |
| pH | Not applicable |
| Melting point/freezing point | > 1200°C |
| Initial boiling point and boiling point range | Not applicable |
| Flash point | Not applicable |
| Evaporation rate | Not Applicable |
| Flammability (solid, gas) | Not applicable |
| Upper/lower flammability or explosive limits | Not applicable |
| Vapour pressure | Not applicable |
| Vapour density | Not Applicable |
| Relative density | 1 - 2 g/cm ³ |
| Solubility(ies) | Slight |
| Partition co-efficient: n-octanol/water | Not applicable |
| Auto-ignition temperature | Not applicable |
| Decomposition temperature | Not Applicable |
| Viscosity | Not Applicable |
| Other safety information | No further relevant information available. |
| Particle Characteristics | Not applicable |
| Explosive properties | Not applicable |
| Oxidising properties | Not applicable |

10 - Stability and Reactivity

10.1 - Reactivity

AES is stable and non reactive

10.2 - Chemical Stability

AES is inorganic, stable and inert

10.3 - Possibility of Hazardous Reactions

None

10.4 - Conditions to Avoid

Please refer to handling and storage advice in Section 7

10.5 - Incompatible Materials

None

10.6 - Hazardous decomposition products

Upon heating above 900°C for sustained periods, this amorphous material begins to transform to mixtures of crystalline phases. For further information please refer to Section 16.

11 - Toxicological information

Toxicokinetics, metabolism and distribution

11.1.1 BASIC TOXICOKINETICS

Exposure is predominantly by inhalation or ingestion. Man made vitreous fibres of a similar size to AES have not been shown to migrate from the lung and/or gut and do not become located in other organs of the body

Fibres contained in the products listed in the title have been designed to be rapidly cleared from lung tissue. This low biopersistence has been confirmed in many studies on AES using EU protocol ECB/TM/27(rev 7). When inhaled, even at very high doses, they do not accumulate to any level capable of producing a serious adverse biological effect.

11.1 - Information on hazard classes as defined in Regulation (EC) No 1272/2008

In lifetime chronic studies there was no exposure-related effect more than would be seen with any "inert" dust. Subchronic studies at the highest doses achievable produced at worst a transient mild inflammatory response. Fibres with the same ability to persist in tissue do not produce tumours when injected into the peritoneal cavity of rats.

Superwool fibres are negative when tested using approved methods (OECD TG 404). Like all man-made mineral fibres and some natural fibres, fibres contained in this product can produce a mild mechanical irritation resulting in temporary itching or rarely, in some sensitive individuals, in a slight temporary reddening. Unlike other irritant reactions this is not the result of allergy or chemical skin damage but is caused by mechanical effects.

12 - Ecological information

12.1 - Toxicity

These products are inert materials that remain stable overtime.
No adverse effects of this material on the environment are anticipated.

12.2 - Persistence and degradability

Not established

12.3 - Bioaccumulative potential

Not established

12.4 - Mobility in soil

No information available

12.5 - Results of PBT and vPvB assessment

This mixture contains no substance considered to be persistent, bioaccumulating nor toxic (PBT).

This mixture contains no substance considered to be very persistent and very bioaccumulative (vPvB).

12.6 - Endocrine Disrupting Properties

No additional information available

12.7 - Other adverse effects

13 - Disposal Considerations

13.1 - Disposal Considerations

To prevent waste materials from becoming airborne during waste storage, transportation and disposal, a covered container or plastic bagging is recommended.

For Australia, waste from these materials should be considered as hazardous waste and local waste authorities should be contacted for correct disposal methods.

For other countries, waste from these materials (even after use above 900°C) is not classified as hazardous waste and may generally be disposed of at a normal tipping site which has been licensed for the disposal of industrial waste. Taking into account any possible contamination during use, which may be classified as hazardous, expert guidance should be sought.

Such a waste is normally dusty (unless wetted) and so should be properly bagged and clearly labelled for disposal. At some tip sites dusty waste may be treated differently in order to ensure they are dealt with promptly and to avoid them being windblown. Check for national and /or regional regulations to identify all applicable disposal requirements.

14 - Transport information

14.1 - Transport information

14.1. UN number

Not Applicable

14.2. UN proper shipping name

Not Applicable

14.3. Transport hazard class(es)

Not Applicable

14.4. Packing group

Not Applicable

14.5. Environmental hazards

Not Applicable

14.6. Special precautions for user

Not Applicable

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not Applicable

15 - Regulatory information

15.1 - Regulatory information

This SDS has been prepared in accordance with WHO GHS rev. 6 requirements. Where applicable, local regulations have been followed.

16 - Other Information

16.1 - ADDITIONAL INFORMATION AND PRECAUTIONS TO BE CONSIDERED UPON REMOVAL OF AFTER SERVICE MATERIAL

16.2 - uses advised against

16.3 - NOTE

This Safety Data Sheet was originally produced in English and has subsequently been translated in to other languages; whilst every effort has been made to make this an accurate translation, please be aware that technical terms do not always translate correctly. The English version should always be considered as the reference version.

16.4 - Further Information

FURTHER INFORMATION

Further information can be found on

<http://www.morganthermalceramics.com/>

<http://www.cdc.gov/niosh/docs/2006-123/>

<http://www.ecfia.eu/>

http://echa.europa.eu/chem_data/authorisation_process/candidate_list_obligations_en.asp

16.5 - Technical Datasheets

TECHNICAL DATA SHEETS

For more information on individual products please see the technical data sheet section at www.morganthermalceramics.com

16.6 - Revision Summary

Update to section 3

16.7 - NOTICE

The information presented herein is based on data considered to be accurate as of the date of preparation of this Safety Data Sheet. However, no warranty or representation, express or implied, is made as to the accuracy or completeness of the foregoing data and safety information, nor is any authorization given or implied to practice any patented invention without a license. In addition, no responsibility can be assumed by the vendor for any damage or injury resulting from abnormal use, from any failure to adhere to recommended practices, or from any hazards inherent in the nature of the product.