

SAFETY DATA SHEET

(Following Regulations (EC) No 1907/2006 & (EC) No 1272/2008)

SDS Number: 613 Date of first issue: 08 December 2014 Date of last revision: 21 February 2022

1 - Identification of product

1.1 - Identification of Product

Tradenames: FB 10,

1.2 - Use of Product

Application as high temperature processing, lining of industrial furnaces, thermal insulation of kilns, etc... (Please refer to specific technical data sheet for more information).

1.3 - Identification of Company

U.K. THERMAL CERAMICS LIMITED
Tebay Road, Bromborough
Wirral, Merseyside CH62 3PH
Tel. : +44 (0) 151 334 4030
Fax : +44 (0) 151 334 1684

Website

www.morganthermalceramics.com
sds.tc@morganplc.com

1.4 - Emergency information

Tel: + 44 (0) 7931 963 973
Language: English
Opening hours: Only available during office hours

2 - Hazard Identification

2.1 - Classification of the substance/ mixture

2.1.1 CLASSIFICATION ACCORDING TO REGULATION (EC) NO 1272/2008

Classified as category 1 damaging to eyes, category 2 skin irritant, category 3 respiratory irritant and category 1 skin sensitizer

2.2 - Labelling Elements

2.2.1 LABELLING ELEMENTS ACCORDING TO REGULATION (EC) NO 1272/2008



Hazard pictogram: GHS05
Signal Word: Danger
Hazard statements:
H315: Causes skin irritation
H318: Causes serious eye damage
H317: May cause an allergic skin reaction
H335: May cause respiratory irritation

Precautionary Statements

P280: Wear protective gloves/protective clothing/eye protection/
face protection.

P305 + P351 + P338 + P310:IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.

P362 + P352 + P333 + P313:IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention.

P261 + P304 + P340 + P312:Avoid breathing dust/fume/gas/mist/vapours/spray. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

P501: Dispose of contents/container to in accordance with local requirements

2.3 - Other hazards which do not result in classification

Mild mechanical irritation to skin, eyes and upper respiratory system may result from exposure.
These effects are usually temporary.
When mixed with water, an increase in pH will occur. Alkaline mix may be irritating to skin and could cause damage to eyes.

CHRONIC RESPIRATORY HEALTH EFFECTS

These products may contain minimal amounts of crystalline silica. Prolonged/repeated inhalation of respirable crystalline silica dust may cause delayed lung injury (silicosis). IARC (International Agency for Research on Cancer) states that there is "sufficient evidence in humans for the carcinogenicity of inhaled crystalline silica in the form of quartz or cristobalite from occupational sources to classify crystalline silica as carcinogenic to humans (Group 1)" (Monograph V 68). In making the overall evaluation the Working Group noted however that carcinogenicity in humans was not detected in all industrial circumstances studied.

3 - Composition / Information On Ingredients

The above-mentioned products are dry refractory powders.

| Component | % by weight | CAS No. | REACH Registration Number | Hazard Classification according to CLP |
|------------------------------|-------------|---------------|---------------------------|--|
| Cement | 35-45 | 65997-15-1 | Not yet available | H315, H318, H317, H335 |
| Clay | 25-35 | 1332-58-7 | Not yet available | Not classified |
| Alumino silicate | 5-15 | Not available | Not yet available | Not classified |
| Other inert mineral material | 45-55 | Not available | Not yet available | Not classified |

None of the components are radioactive under the terms of European Directive Euratom 96/29.

4 - First-Aid measures

4.1 - Description of First Aid Measures.

Skin

In case of skin irritation rinse affected areas with water and wash gently. Do not rub or scratch exposed skin.

Eyes

In case of eye contact flush abundantly with water; have eye bath available. Do not rub eyes. Seek medical attention if irritation persists.

Nose and Throat

If these become irritated move to a dust free area, drink water and blow nose. Seek medical attention if irritation persists.

If symptoms persist, seek medical advice.

4.2 - Most important symptoms and effects, both acute and delayed

No symptoms or effects expected either acute or delayed

4.3 - Indication of any immediate medical attention and special treatment required

No special treatment required, if exposure occurs wash exposed areas to avoid irritation.

5 - Fire-fighting measures

5.1 - Extinguishing media

Use extinguishing agent suitable for surrounding combustible materials.

5.2 - Special hazards arising from the substance or mixture

Non-combustible products,

5.3 - Advice for firefighters

Packaging and surrounding materials may be combustible.

6 - Accidental Release Measures

6.1 - Personal precautions, protective equipment and emergency procedures

Wear suitable goggles, gloves and protective clothing.

6.2 - Environmental precautions

Prevent further dust dispersion for example by dampening the materials

Avoid clean up procedure that could result in water pollution.

Do not flush spillage to drain.

Check for local regulations, which may apply.

6.3 - Methods and materials for containment and clean up

Contain spillage, absorb in earth or sand and shovel into suitable containers

6.4 - Reference to other sections

7 - Handling and storage

7.1 - Precautions for safe handling

Do not handle wet product with bare hands. Handling of dried products can be a source of dust emission and therefore the processes should be designed to limit the amount of handling.

Whenever possible, handling should be carried out under controlled conditions (i.e., using dust exhaust system).

Regular good housekeeping will minimise secondary dust dispersal.

7.2 - Conditions for safe storage

Store in original packaging in dry area whilst awaiting use

Avoid damaging packaging.

Recyclable cardboard and/or plastic films are recommended for packaging.

7.3 - Specific end use

Please refer to your local Morgan Thermal Ceramics' supplier.

8 - Risk Management Measures / Exposures Controls / Personal Protection

8.1 - Control parameters

Removing dried material after use may generate respirable dust.

Industrial hygiene standards and occupational exposure limits vary between countries and local jurisdictions. Check which exposure levels apply to your facility and comply with local regulations. If no regulatory dust or other standards apply, a qualified industrial hygienist can assist with a specific workplace evaluation including recommendations for respiratory protection.

Examples of national OELs (November 2014) are given in the table below. Additional references and/or updates can be found on the following websites:

http://www.dguv.de/ifa/en/gestis/limit_values

<http://osha.europa.eu/en/publications/reports/548OELs/view>

| COUNTRY | Total Dust (mg/m ³) | Resp Dust (mg/m ³) | Quartz (mg/m ³) | Cristobalite (mg/m ³) |
|----------------|---------------------------------|--------------------------------|-----------------------------|-----------------------------------|
| Austria | 10 | 6 | 0.15 | 0.15 |
| Belgium | 10 | 3 | 0.10 | 0.05 |
| Czech Republic | No limit | No limit | 0.10 | 0.10 |
| Denmark | 10 | 5 | 0.10 | 0.05 |
| Finland | No limit | No limit | 0.20 | 0.10 |
| France | 1 | 5 | 0.10 | 0.05 |
| Germany* | 10 | 3 | No limit | No limit |
| Greece | 10 | 5 | 0.10 | 0.05 |
| Hungary | No limit | No limit | 0.15 | 0.10 |
| Ireland | 10 | 4 | 0.05 | 0.05 |
| Italy | 10 | 3 | 0.025 | 0.025 |
| Luxembourg | 10 | 6 | 0.15 | 0.15 |
| Netherlands | 10 | 5 | 0.075 | 0.075 |
| Norway | 10 | 5 | 0.10 | 0.05 |
| Poland | No limit | No limit | 0.30 | 0.30 |
| Portugal | 10 | 5 | 0.025 | 0.025 |
| Romania | 10 | 10 | 0.10 | 0.05 |
| Spain | 10 | 3 | 0.10 | 0.05 |
| Sweden | 10 | 5 | 0.10 | 0.05 |
| Switzerland | 10 | 6 | 0.15 | 0.15 |
| UK | 10 | 4 | 0.10 | 0.10 |

* Gravimetric concentrations of respirable dust – 8-hour time weighted average.

Information on monitoring procedures

United Kingdom

MDHS 14/4 - "General methods for sampling and gravimetric analysis of respirable, thoracic and inhalable aerosols"

MDHS 101 - "Crystalline silica in respirable airborne dusts"

NIOSH

NIOSH 0500 "Particulates not otherwise regulated, total"

NIOSH 0600 "Particulates not otherwise regulated, respirable"

NIOSH 7500 "Silica, Crystalline, by XRD (filter redeposition)"

8.2 - Exposure controls

8.2.1 APPROPRIATE ENGINEERING CONTROLS

Review your applications in order to identify potential sources of dust exposure.

Local exhaust ventilation, which collects dust at source, can be used. For example down draft tables, emission controlling tools and materials handling equipment.

Keep the workplace clean. Use a vacuum cleaner. Avoid brushing and compressed air.

If necessary, consult an industrial hygienist to design workplace controls and practices.

The use of products specially tailored to your application(s) will help to control dust. Some products can be delivered ready for use to avoid further cutting or machining. Some could be pre-

treated or packaged to minimise or avoid dust release during handling.

Consult your supplier for further details

8.2.2 - Personal Protective Equipment

Skin protection:

Use of gloves and work clothes is recommended.

Soiled clothes should be cleaned before being taken off (e.g. use vacuum cleaning, not compressed air).

Eye protection:

As necessary wear goggles or safety glasses with side shields.

Respiratory protection:

For dust concentrations below the exposure limit value, RPE is not required but FFP2 respirators may be used on a voluntary basis.

For short-term operations where excursions are less than ten times the limit value use FFP2 respirators.

In case of higher concentrations or where the concentration is not known, please seek advice from your company and/or local Thermal Ceramics' supplier.

INFORMATION AND TRAINING OF WORKERS

Workers should be trained on good working practices and informed on applicable local regulations

8.2.3 - Environmental Exposure Controls

Refer to local, national or European applicable environmental standards for release to air water and soil.

For waste, refer to section13

9 - Physical and chemical properties

| | |
|---|--------------------------------|
| Information on basic physical and chemical properties | Not applicable |
| State | Grey Powder |
| Colour | Not applicable |
| Odour | None |
| Odour threshold | Not Applicable |
| pH | 8 - 12 (when mixed with water) |
| Melting point/freezing point | > 1100°C |
| Initial boiling point and boiling point range | Not applicable |
| Flash point | Not applicable |
| Evaporation rate | Not Applicable |
| Flammability (solid, gas) | Not applicable |
| Upper/lower flammability or explosive limits | Not applicable |
| Vapour pressure | Not applicable |
| Vapour density | Not Applicable |
| Relative density | 400 - 550 kg/m ³ |
| Solubility(ies) | slight |
| Partition co-efficient: n-octanol/water | Not applicable |
| Auto-ignition temperature | Not applicable |
| Decomposition temperature | Not Applicable |
| Viscosity | Not Applicable |
| Particle Characteristics | Not applicable |
| Explosive properties | Not applicable |
| Oxidising properties | Not applicable |

10 - Stability and Reactivity

10.1 - Reactivity

The product is stable

10.2 - Chemical Stability

The product is inorganic, stable and inert

10.3 - Possibility of Hazardous Reactions

None

10.4 - Conditions to Avoid

Please refer to handling and storage advice in Section 7

10.5 - Incompatible Materials

None

10.6 - Hazardous decomposition products

Upon heating above 900°C for sustained periods, this amorphous material begins to transform to mixtures of crystalline phases. For further information please refer to Section 16.

11 - Toxicological information

Toxicokinetics, metabolism and distribution

11.1.1 BASIC TOXICOKINETICS

As manufactured, these products may contain a minimal amount of crystalline silica. Exposure is predominantly by inhalation or ingestion, available toxicological information is as follows:

11.1.2 Human Toxicological data

Epidemiology for crystalline silica

Prolonged/repeated inhalation of respirable crystalline silica dust may cause delayed lung injury (silicosis).

In evaluating crystalline silica as a cancer risk, the International Agency for Research on Cancer (IARC) reviewed several studies from different industries and concluded that crystalline silica from occupational sources inhaled in the form of quartz or cristobalite is carcinogenic to humans (Group 1) [IARC Monograph; vol.68; June 1997]. However, in reaching its conclusion, IARC stated that the carcinogenicity in humans could not be found in all industries reviewed and that carcinogenicity might be dependent on inherent characteristics of crystalline silica or on external factors affecting biological activity (e.g., cigarette smoking) or distribution of its polymorphs.

11.1 - Information on hazard classes as defined in Regulation (EC) No 1272/2008

Experimental studies for crystalline silica

Animals exposed to very high concentrations of crystalline silica, artificially or by inhalation, have reported fibrosis and tumours (IARC Monographs 42 and 68).

Inhalation and intratracheal installation of crystalline silica in rats caused lung cancer. However, studies in other species such as mice and hamsters caused no lung cancer. Crystalline silica also caused fibrosis in rats and hamsters in several inhalation and intratracheal installation studies.

ACUTE TOXICITY

Lethal dose 50 % (LD50) / lethal concentration 50% (LC50): N.A.

12 - Ecological information

12.1 - Toxicity

These products are inert materials that remain stable overtime.
No adverse effects of this material on the environment are anticipated.

12.2 - Persistence and degradability

Not established

12.3 - Bioaccumulative potential

Not established

12.4 - Mobility in soil

No information available

12.5 - Results of PBT and vPvB assessment

This mixture contains no substance considered to be persistent, bioaccumulating nor toxic (PBT).

This mixture contains no substance considered to be very persistent and very bioaccumulative (vPvB).

12.6 - Endocrine Disrupting Properties

No additional information available

12.7 - Other adverse effects

13 - Disposal Considerations

Waste from these materials may be generally disposed off at a landfill, which has been licensed for this purpose. Please refer to the European list (Decision N° 2000/532/CE as modified) to identify your appropriate waste number, and insure national and/or regional regulations are complied with.

Unless wetted, such a waste is normally dusty and so should be properly sealed in containers for disposal. At some authorised disposal sites, dusty waste may be treated differently in order to ensure they are dealt with promptly to avoid them being windblown. Check for any national and/or regional regulations, which may apply.

14 - Transport information

14.1. UN number

Not Applicable

14.2. UN proper shipping name

Not Applicable

14.3. Transport hazard class(es)

Not Applicable

14.4. Packing group

Not Applicable

14.5. Environmental hazards

Not Applicable

14.6. Special precautions for user

Not Applicable

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not Applicable

15 - Regulatory information

15.1 - Safety health and environment regulations/legislation specific for the substances or mixtures

EU regulations:

- Regulation (EC) No 1907/2006 dated 18th December 2006 on Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)
- Regulation (EC) No 1272/2008 dated 20th January 2009 on classification, labelling and packaging of substances and mixtures (OJ L 353)
- Annex of Regulation (EU) 2015/830
- Commission regulation (EC) No 790/2009 of 10 August 2009 amending, for the purposes of its adaptation to technical and scientific progress, Regulation (EC) No 1272/2008 of the European Parliament and of the Council on classification, labelling and packaging of substances and mixtures.
- The 1st Adaptation to Technical Progress (ATP) to Regulation (EC) No 1272/2008 enters into force on 25 September 2009.

PROTECTION OF WORKERS

Shall be in accordance with several European Directives as amended and their implementations by the Member States:

- a) Council Directive 89/391/EEC dated 12 June 1989 "on the introduction of measures to encourage improvements in the safety and health of workers at work" (OJEC (Official Journal of the European Community) L 183 of 29 June 1989, p.1).
- b) Council Directive 98/24/EC dated 7 April 1998 "on the protection of workers from the risks related to chemical agents at work" (OJEC L 131 of 5 May 1998, p.11).

OTHER POSSIBLE REGULATIONS

Member States are in charge of implementing European Directives into their own national regulation within a period of time normally given in the Directive. Member States may impose more stringent requirements. Please always refer to any national regulation.

15.2 - Chemical Safety Assessment

Chemical Safety Reports have been requested from suppliers, as soon as this information is available it will be shared with downstream users.

16 - Other Information

Full text for H Phrases found in Section 3:

H315: Causes skin irritation
H318: Causes serious eye damage
H317: May cause an allergic skin reaction
H335: May cause respiratory irritation

Additional information and precautions to be considered upon removal of after service material

Continuous use of these products at temperatures above 900°C may, as with many other refractories, lead to the formation of cristobalite (a type of crystalline silica). Please refer to sections 2, 11 and to national regulation on crystalline silica.

High concentrations of dusts may be generated when after-service products are mechanically disturbed during operations such as wrecking. Therefore Morgan Thermal Ceramics recommends:

- a) control measures are taken to reduce dust emissions;
- b) all personnel directly involved wear an appropriate respirator to minimise exposure; and
- c) Compliance with local regulatory limits.

For more information connect to:

The Morgan Thermal Ceramics' website: (<http://www.morganthermalceramics.com/>)

Or ECFIA's website: (<http://www.ecfia.eu>)

Revision Summary

Update to Section 8

Technical data sheets

NOTICE:

The information presented herein is based on data considered to be accurate as of the date of preparation of this Material Safety Data Sheet. However safe as provided by law, no warranty or representation, express or implied, is made as to the accuracy or completeness of the foregoing data and safety information, nor is any authorisation given or implied to practice any patented invention without a licence. In addition, no responsibility can be assumed by the vendor for any damage or injury resulting from abnormal use, from any failure to adhere to recommended practices, or from any hazards inherent in the nature of the product (however, this shall not act to restrict the vendor's potential liability for negligence or under statute).