

#### SAFETY DATA SHEET

(Following Regulations (EC) No 1907/2006 & (EC) No 1272/2008)

SDS Number: 442 Date of first issue: 13 February 2020 Date of last revision: 21 February 2022

#### 1 - Identification of product

#### 1.1 - Identification of Product

Tradenames: EST Compression Paper,

The above-mentioned product contains Alkaline-earth silicate wools (AES wools) Index Number: 650-016-00-2 Annex VI

CAS number: 436083-99-7

Registration number: 01-2119457644-32-0000

## 1.2 - Use of Product

Fire retardant, passive fire protection, thermal insulation and electric insulation for lithium ion battery

#### 1.3 - Identification of Company

IDENTIFICATION OF THE MANUFACTURER/SUPPLIER

Murugappa Morgan Thermal Ceramics Ltd., Plot No: 26 & 27, SIPCOT Industrial complex, Ranipet, Vellore District, Tamil Nadu, India Pin: 632403

Website

www.morganthermalceramics.com sds.tc@morganplc.com

## 1.4 - Emergency information

**EMERGENCY CONTACT NUMBER** 

Tel 1: +91 (4172) 244 313 extn no. 215 or 201 Language: English

Opening hours: Only available during office hours

2 - Hazard Identification

## 2.1 - Classification of the substance/ mixture

2.1.1 CLASSIFICATION ACCORDING TO REGULATION (EC) NO 1272/2008

Not classified as hazardous according to Classification, Labelling and Packaging regulations (CLP) 1272/2008 EEC

## 2.2 - Labelling Elements

Not applicable

## 2.3 - Other hazards which do not result in classification

Mild mechanical irritation to skin, eyes and upper respiratory system may result from exposure. These effects are usually temporary

## 3 - Composition / Information On Ingredients

These products are papers made from acrylic bound AES wool.

COMPONENT	% by weight	CAS No.	REACH Registration Number	Hazard Classification according to CLP
Alkaline-earth silicate wools	50-65	436083-99-7	01-2119457644-32	Note Q exonerated
Inert Inorganic binder	10-20	Not Applicable	Not yet available	Not classified as hazardous
Acrylic Polymer	25-35	Not Applicable	Not yet available	Not classified as hazardous

Murugappa Morgan Thermal Ceramics Ltd., Plot No: 681, Motibhoyan Village, Sanand-Kalol state Highway, Kalol Taluk, Gandhi Nagar District, Gujarat, India

#### 4 - First-Aid measures

# Skin

Handling of this material may generate mild mechanical temporary skin irritation. If this occurs, rinse affected areas with water and wash gently. Do not rub or scratch exposed skin.

In case of eye contact flush abundantly with water; have eye bath available. Do not rub eyes. Seek medical attention is irritation persists.

#### Nose and Throat

If these become irritated move to a dust free area, drink water and blow nose. Seek medical attention if irritation persists.

If symptoms persist, seek medical advice.

#### 4.2 - Most Important symptoms and effects, both acute and delayed

No symptoms or effects expected either acute or delayed

#### 4.3 - Indication of any immediate medical attention and special treatment required

No special treatment required, if exposure occurs wash exposed areas to avoid irritation.

#### 5 - Fire-fighting measures

#### 5.1 - Extinguishing media

Non-combustible products. Fire protection class: 0

Packaging and surrounding materials could be combustible.

Use extinguishing agent suitable for surrounding combustible materials.

#### 5.2 - Special hazards arising from the substance or mixture

Non-combustible products,

#### 5.3 - Advice for firefighters

Packaging and surrounding materials may be combustible.

### 6 - Accidental Release Measures

#### 6.1 - Personal precautions, protective equipment and emergency procedures

Where abnormally high dust concentrations occur, provide the workers with appropriate protective equipment as detailed in section 8.

Restore the situation to normal as guickly as possible.

#### 6.2 - Environmental precautions

Prevent further dust dispersion for example by damping the materials.

Do not flush spillage to drain and prevent from entering natural watercourses.

Check for local regulations, which may apply

## 6.3 - Methods and materials for containment and clean up

Pick up large pieces and use a vacuum cleaner.

If brushes are used, ensure that the area is wetted down first.

Do not use compressed air for clean up.

Do not allow to become windblown.

## 6.4 - Reference to other sections

For further information, please refer to sections 7 and 8

## 7 - Handling and storage

## 7.1 - Precautions for safe handling

Handling can be a source of dust emission and therefore the processes should be designed to limit the amount of handling. Whenever possible, handling should be carried out under controlled conditions (i.e., using dust exhaust system).

Regular good housekeeping will minimise secondary dust dispersal.

## 7.2 - Conditions for safe storage

Packaging should be kept closed and intact to reduce the possibility of releasing dust.

Re-use of packaging is not recommended in case residual fibrous dust and product debris are present.

## 7.3 - Specific end use

The main application of these products is as thermal insulation. Please refer to your local Morgan Thermal Ceramics' supplier.

## 8 - Risk Management Measures / Exposures Controls / Personal Protection

#### 8.1 - Control parameters

Industrial hygiene standards and occupational exposure limits vary between countries and local jurisdictions. Check which exposure levels apply to your facility, and comply with local regulations. If no regulatory dust or other standards apply, a qualified industrial hygienist can assist with a specific workplace evaluation including recommendations for respiratory protection. Examples of exposure limits applying (in November 2014) in different countries are given below:

Country	MMVF	Source	
Austria	1 f/ml	Grenzwerteverordnung	
Belgium	10 mg/m3	Valeurs limites d'exposition professionnelle – VLEP/ Grenswaarden voor beroepsmatige blootstelling – GWBB	
Czech Republic	1 f/ml		
Denmark	1 f/ml	Grænseværdier for stoffer og materialer	
Finland	1 f/ml	Finnish Ministry of Social Affairs and Health	
France	1 f/ml	INRS	
Germany*	1.25 mg/m <sup>3</sup>	TRGS900	
Hungary	1 f/ml	EüM-SZCSM rendelet	
Ireland	1 f/ml	HAS - Eire	
Italy	1 f/ml		
Luxembourg	1 f/ml	Règlement grand-ducal du 30 juillet 2002	
Netherlands	1 f/ml	Social and Economic Council of the Netherlands	
Norway	0.5 f/ml	Veiledning om administrative normer for forurensning i arbeidsatmosfære	
Poland	2 f/ml	Dziennik Ustaw 2010	
Spain	1 f/ml	INSHT	
Sweden	1 f/ml	Hygieniska gränsvärden och åtgärder mot luftföroreningar	
Switzerland	1 f/ml	SUVA	
UK	2 f/ml	EH40/2005	
GCC	1 f/ml	Abu Dhabi OSHAD	
South Africa	5mg/m <sup>3</sup>	Regulation 1179 – Hazardous Chemical Substances 2007	

#### Information on monitoring procedures

#### 8.2 - Exposure controls

## 8.2.1 APPROPRIATE ENGINEERING CONTROLS

Review your applications in order to identify potential sources of dust exposure.

Local exhaust ventilation, which collects dust at source, can be used. For example down draft tables, emission controlling tools and materials handling equipment. Keep the workplace clean. Use a vacuum cleaner. Avoid brushing and compressed air.

If necessary, consult an industrial hygienist to design workplace controls and practices.

The use of products specially tailored to your application(s) will help to control dust. Some products can be delivered ready for use to avoid further cutting or machining. Some could be pretreated or packaged to minimise or avoid dust release during handling. Consult your supplier for further details

## 8.2.2 - Personal Protective Equipment

## Skin protection:

Wear gloves and work clothes, which are loose fitting at the neck and wrists. Soiled clothes should be cleaned to remove excess fibres before being taken off (e.g. use vacuum cleaner, not compressed air). Wash work clothes seperately from other clothing.

## Eve protection:

As necessary wear goggles or safety glasses with side shields.

## Respiratory protection:

For dust concentrations below the exposure limit value, RPE is not required but FFP2 respirators may be used on a voluntary basis.

For short-term operations where excursions are less than ten times the limit value use FFP2 respirators.

In case of higher concentrations or where the concentration is not known, please seek advice from your company and/or local Thermal Ceramics supplier.

Information and training of workers
Workers should be trained on good working practices and informed on applicable local regulations.

## 8.2.3 - Environmental Exposure Controls

Refer to local, national or European applicable environmental standards for release to air water and soil.

For waste, refer to section13

### 9 - Physical and chemical properties

Information on basic physical and chemical properties Not Applicable State White Fibre Colour Not applicable Odour None **Odour threshold** Not Applicable

Not applicable

Melting point/freezing point 1275 - 1300°C (2327 - 2372°F)

Initial boiling point and boiling point range Not applicable Flash point Not applicable **Evaporation rate** Not Applicable Flammability (solid, gas) Not applicable Not applicable Upper/lower flammability or explosive limits Vapour pressure Not applicable Vapour density Not Applicable Relative density >2 T/m<sup>3</sup>

Solubility(ies) Less than 1 mg/l Partition co-efficient: n-octanol/water Not applicable Auto-ignition temperature Not applicable **Decomposition temperature** Not Applicable Viscosity Not Applicable

Other safety information No further relevant information available.

**Particle Characteristics** Not appicable **Explosive properties** Not applicable Not applicable Oxidising properties

10 - Stability and Reactivity

#### 10.1 - Reactivity

AES is stable and non reactive

#### 10.2 - Chemical Stability

AES is inorganic, stable and inert

#### 10.3 - Possibility of Hazardous Reactions

During first heating, oxidation products from the organic binder might be emitted in a temperature range from 180°C to 600°C. It is recommended to ventilate the room until gases and fumes have disappeared. Avoid exposure to high concentrations of gas or fumes.

#### 10.4 - Conditions to Avoid

Please refer to handling and storage advice in Section 7

#### 10.5 - Incompatible Materials

None

## 10.6 - Hazardous decomposition products

Upon heating above 900°C for sustained periods, this amorphous material begins to transform to mixtures of crystalline phases. For further information please refer to Section 16.

## 11 - Toxicological information

## Toxicokinetics, metabolism and distribution

## 11.1.1 BASIC TOXICOKINETICS

Exposure is predominantly by inhalation or ingestion. Man made vitreous fibres of a similar size to AES have not been shown to migrate from the lung and/or gut and do not become located in other organs of the body

Fibres contained in the products listed in the title have been designed to be rapidly cleared from lung tissue. This low biopersistence has been confirmed in many studies on AES using EU protocol ECB/TM/27(rev 7). When inhaled, even at very high doses, they do not accumulate to any level capable of producing a serious adverse biological effect

## - Information on hazard classes as defined in Regulation (EC) No 1272/2008

In lifetime chronic studies there was no exposure-related effect more than would be seen with any "inert" dust. Subchronic studies at the highest doses achievable produced at worst a transient mild inflammatory response. Fibres with the same ability to persist in tissue do not produce tumours when injected into the peritoneal cavity of rats.

## 12 - Ecological information

## 12.1 - Toxicity

These products are insoluble materials that remain stable overtime and are chemically identical to inorganic compounds found in the soil and sediment; they remain inert in the natural No adverse effects of this material on the environment are anticipated.

## 12.2 - Persistence and degradability

Not established

## 12.3 - Bioaccumulative potential

Not established

## 12.4 - Mobility in soil

No information available

## 12.5 - Results of PBT and vPvB assessment

This mixture contains no substance considered to be persistent, bioaccumulating nor toxic (PBT).

This mixture contains no substance considered to be very persistent and very bioaccumulative (vPvB).

## 12.6 - Endocrine Disrupting Properties

No additional information available

## 12.7 - Other adverse effects

## 13 - Disposal Considerations

#### 13.1 - Disposal Considerations

To prevent waste materials from becoming airborne during waste storage, transportation and disposal, a covered container or plastic bagging is recommended.

For Australia, waste from these materials should be considered as hazardous waste and local waste authorities should be contacted for correct disposal methods.

For other countries, waste from these materials (even after use above 900°C) is not classified as hazardous waste and may generally be disposed of at a normal tipping site which has been licensed for the disposal of industrial waste. Taking into account any possible contamination during use, which may be classified as hazardous, expert guidance should be sought.

Such a waste is normally dusty (unless wetted) and so should be properly bagged and clearly labelled for disposal. At some tip sites dusty waste may be treated differently in order to ensure they are dealt with promptly and to avoid them being windblown. Check for national and /or regional regulations to identify all applicable disposal requirements.

#### 14 - Transport information

#### 14.1 - Transport information

#### 14.1. UN number

Not Applicable

## 14.2. UN proper shipping name

Not Applicable

#### 14.3. Transport hazard class(es)

Not Applicable

## 14.4. Packing group

Not Applicable

#### 14.5. Environmental hazards

Not Applicable

#### 14.6. Special precautions for user

Not Applicable

## 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not Applicable

### 15 - Regulatory information

#### 15.1 - Regulatory information

The fibres contained in this product have been tested for bio persistance according to Note Q requirements under European Classification, Labelling and Packaging Regulations (EC/1272/2008) and it's subsequent amendments.

Based on these results they are exonerated from classification as carcinogens in Europe and Australia.

#### 16 - Other Information

#### 16.1 - ADDITIONAL INFORMATION AND PRECAUTIONS TO BE CONSIDERED UPON REMOVAL OF AFTER SERVICE MATERIAL

## 16.2 - uses advised against

## 16.3 - NOTE

This Safety Data Sheet was originally produced in English and has subsequently been translated in to other languages; whilst every effort has been made to make this an accurate translation, please be aware that technical terms do not always translate correctly. The English version should always be considered as the reference version.

## 16.4 - Further Information

## FURTHER INFORMATION

Further information can be found on

http://www.morganthermalceramics.com/

http://www.ecfia.eu/

http://www.safeworkaustralia.gov.au/sites/swa/about/publications/pages/workplace-exposure-standards-airborne-contaminants

## 16.5 - Technical Datasheets

## TECHNICAL DATA SHEETS

For more information on individual products please see the technical data sheet section at www.morganthermalceramics.com

## 16.6 - Revision Summary

New Safety Data Sheet

## 16.7 - NOTICE

The information presented herein is based on data considered to be accurate as of the date of preparation of this Safety Data Sheet. However, no warranty or representation, express or implied, is made as to the accuracy or completeness of the foregoing data and safety information, nor is any authorization given or implied to practice any patented invention without a license. In addition, no responsibility can be assumed by the vendor for any damage or injury resulting from abnormal use, from any failure to adhere to recommended practices, or from any hazards inherent in the nature of the product.